



## MATERIAL FACT SHEET

### 279291 TH-T18KP 2.5A

#### General Data

Product Hierarchy	IAN50203
	MC
	TH-T Body
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	B (Limited Availability from Stock)

e-shop: <https://emea.mitsubishielectric.com/fa/shop/material-page/000000000000279291>

#### FA-MC: Overload Protection Relays

Series	MS-T THERMAL OVERLOAD RELAY
Type	WITH 3-ELEMENT (2E)
Heater Designation (A)	2.5
Range of Setting Current (A)	2 - 3
Rated Capacity (kW)	3-PHASE 220-240V: -
Rated Capacity (kW) (2)	3-PHASE 380-440V: 1,1
Rated Voltage (V)	690
Frequency Range (Hz)	0(DC) - 400
Min. Ambient Temperature (°C)	-10
Max. Ambient Temperature (°C)	+40
No of Auxiliary Contacts NO	1
No of Auxiliary Contacts NC	1

#### Product Dimensions & Weight

Width (mm)	45
Height (mm)	55
Depth (mm)	76,5
Weight (kg)	0,11

#### Logistic Dimensions & Gross Weight

Length (cm)	6,0
Width (cm)	5,0
Height (cm)	8,0
Gross Weight (kg)	0,127
Volume (cdm)	0,240

#### Stock Data

Planned Delivery Time (Days)	203
------------------------------	-----

#### Life Cycle

Sales Start	28.11.2014
Predecessor	No Predecessor

#### Additional Product Information

Battery included	NO
Product Code	MS

#### Export Data

Commodity Code	85365019
Legal Control (Dual Use List)	Not Listed
Country of Origin	Japan (JP)
Preference Status (Supplier Declaration)	Non EU

#### Environmental

REACH Limit Exceeded	NO
Dangerous Goods Class	NO

Dangerous Goods Identifier	NO
RoHS Compliance	COMPLIANT
WEEE	B2B

### Conformity

CE	COMPLIANT
UL/cUL	COMPLIANT
EAC	NON-COMPLIANT
UKCA	COMPLIANT

### Documentation & Media Data

Manual URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2f94&amp;q=TH-T18KP%202.5A&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2f94&amp;q=TH-T18KP%202.5A&amp;doc-lang=en</a>
Certificates URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=TH-T18KP%202.5A&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=TH-T18KP%202.5A&amp;doc-lang=en</a>
CAD URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt26ecc97a31a841c1&amp;q=TH-T18KP%202.5A&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt26ecc97a31a841c1&amp;q=TH-T18KP%202.5A&amp;doc-lang=en</a>

### Product Packaging

Cardboard (g)	200
Other paper (g)	10
Aluminum (g)	0
Steel (g)	0
Styrofoam (g)	0
Other plastic (g)	0
Wood (g)	0
Glass (g)	0
Others (g)	0

### Compatible products

Material	Description / Price List Text / Classification
<a href="#">293229</a>	UT-HZ18 Separate mounting adaptor for Thermal Overload Relays TN-T18 Class 100101003: FA-MC: Electrical Option