



MATERIAL FACT SHEET

411352 BVW-T 2P 80A300M

General Data

Product Hierarchy	IAN40102
	RCCB
	BVW-T
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	C (Non-Stock Material / Make-to-Order)

e-shop: https://mitsubishi-electric-eshop.mee.com/mee/FA_IA/EUR/en/p/000000000000411352

FA-MCB: Residual Current Circuit Breaker

Series	WS-V SERIES - RCCB
Type	BVW-T EARTH CIRCUIT BREAKER
Rated Current (A)	80
Rated Voltage (V)	240
Current Type	AC
Number of Poles	1+N
Breaking Capacity at 415V (kA)	-
Cycles with Rated Current	2000
Cycles without Rated Current	3000
Rated Current Sensibility (mA)	300
Pulsating Current Sensibility	TYPE AC

Product Dimensions & Weight

Width (mm)	36
Height (mm)	90
Depth (mm)	74
Weight (kg)	0,22

Logistic Dimensions & Gross Weight

Length (cm)	10,0
Width (cm)	8,0
Height (cm)	5,0
Gross Weight (kg)	0,248
Volume (cdm)	0,400

Stock Data

Planned Delivery Time (Days)	89
------------------------------	----

Life Cycle

Sales Start	15.01.2019
Predecessor	No Predecessor

Additional Product Information

Battery included	NO
------------------	----

Export Data

Legal Control (Dual Use List)	Not Listed
Country of Origin	India (IN)
Preference Status (Supplier Declaration)	Non EU

Environmental

Dangerous Goods Class	NO
Dangerous Goods Identifier	NO
RoHS Compliance	COMPLIANT
WEEE	B2C

Conformity

CE	COMPLIANT
----	-----------

Documentation & Media Data

Manual URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=bltdae25c2bd5f2ff94&q=BVW-T%202P%2080A300M&doc-lang=en
Certificates URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt8050dd1408c11cc2&q=BVW-T%202P%2080A300M&doc-lang=en
CAD URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt26ecc97a31a841c1&q=BVW-T%202P%2080A300M&doc-lang=en