



MATERIAL FACT SHEET

255458 Q64TCRTBWN

General Data

Product Hierarchy	IAD50702
	Modular PLC
	Q-Single
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	C (Non-Stock Material / Make-to-Order)

e-shop: https://mitsubishi-electric-eshop.mee.com/mee/FA_IA/EUR/en/p/000000000000255458

FA-MOD PLC: Temperature Module

Series	MELSEC-Q SERIES
Type	TEMPERATURE CONTROL
Occupied I/O Points on PLC	32
Integrated Analogue Inputs	4
Input Type	RTD
Applicable RTD Type	JPT100
Applicable RTD Type (2)	PT100
Int. Current Consumption (A)	0,33

Product Dimensions & Weight

Width (mm)	55
Height (mm)	98
Depth (mm)	112
Weight (kg)	0,3

Logistic Dimensions & Gross Weight

Length (cm)	18,0
Width (cm)	15,5
Height (cm)	13,5
Gross Weight (kg)	0,408
Volume (cdm)	3,767

Stock Data

Planned Delivery Time (Days)	75
------------------------------	----

Life Cycle

Sales Start	18.11.2012
Predecessor	136387 / Q64TCRTBW

Additional Product Information

Binding Tariff Information	DEBTI-10685/21-1
BTI validity date	31.10.2024
Battery included	NO

Export Data

Legal Control (Dual Use List)	Not Listed
Country of Origin	Japan (JP)
Preference Status (Supplier Declaration)	Non EU

Environmental

Dangerous Goods Class	NO
Dangerous Goods Identifier	NO
WEEE	B2B

Conformity

CE	COMPLIANT
----	-----------

UL/cUL	COMPLIANT
EAC	COMPLIANT
Shipping Approvals	ABS,BV,DNV GL,LR,NK,RINA
UKCA	COMPLIANT

Documentation & Media Data

Manual URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=bltdae25c2bd5f2ff94&q=Q64TCRTBWN&doc-lang=en
Certificates URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt8050dd1408c11cc2&q=Q64TCRTBWN&doc-lang=en
CAD URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt26ecc97a31a841c1&q=Q64TCRTBWN&doc-lang=en

Product Packaging

Cardboard (g)	75
Other paper (g)	1
Aluminum (g)	0
Steel (g)	0
Styrofoam (g)	0
Other plastic (g)	33
Wood (g)	0
Glass (g)	0
Others (g)	0