



MATERIAL FACT SHEET

283572 FFR-HEL-H22K-E1

General Data

Product Hierarchy	IAK21201
	INVERTER
	NEW EXTERNAL OPTIONS
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	B (Limited Availability from Stock)

e-shop: https://mitsubishi-electric-eshop.mee.com/mee/FA_IA/EUR/en/p/000000000000283572

FA-Inverter: Choke

Type	DC LINK CHOKE
Applicable Inverter	FR-A741
Applicable Inverter (2)	FR-A800
Applicable Inverter (3)	FR-D700-SC
Applicable Inverter (4)	FR-E800
Applicable Inverter (5)	FR-F800
Rated Voltage (V)	400
Current Type	DC
Inductance (mH)	1,35
Rated Capacity (kW)	22
Rated Current (A)	40,5
Power Loss (W)	40,5
Protection Class	IP20

Product Dimensions & Weight

Width (mm)	172
Height (mm)	107
Depth (mm)	166
Weight (kg)	5,3

Logistic Dimensions & Gross Weight

Length (cm)	20,0
Width (cm)	20,0
Height (cm)	21,0
Gross Weight (kg)	6,164
Volume (cdm)	8,400

Stock Data

Planned Delivery Time (Days)	42
------------------------------	----

Life Cycle

Sales Start	30.01.2015
Predecessor	238352 / FFR-HEL-H22K-E

Additional Product Information

Battery included	NO
Forecast Breakdown	ACCESSORIES/DC CHOKES

Export Data

Commodity Code	85049090
Legal Control (Dual Use List)	Not Listed
Country of Origin	Slovenia (SI)
Preference Status (Supplier Declaration)	Non EU

Environmental

REACH Limit Exceeded	NO
----------------------	----

Dangerous Goods Class	NO
Dangerous Goods Identifier	NO
RoHS Compliance	COMPLIANT
WEEE	B2B

Conformity

CE	COMPLIANT
----	-----------

Documentation & Media Data

Manual URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=bltdae25c2bd5f2ff94&q=FFR-HEL-H22K-E1&doc-lang=en
Certificates URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt8050dd1408c11cc2&q=FFR-HEL-H22K-E1&doc-lang=en