MITSUBISHI ELECTRIC EUROPE B.V.

Industrial Automation
Mitsubishi-Electric-Platz 1 40882 Ratingen Deutschland
Telefon +49 (0) 2102 486-0 Fax +49 (0) 2102 486-1120
https://emea.mitsubishielectric.com/fa



MATERIAL FACT SHEET

291974 BHW-T10 2P Type C 6A

General Data

Product Hierarchy	IAN30101
	MCB
	BHW-T10
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	A (Available from Stock)

e-shop: https://mitsubishi-electric-eshop.mee.com/mee/FA_IA/EUR/en/p/000000000000291974

FA-MCB: Miniature Circuit Breaker

Series	WS-V SERIES - MCB
Type	BHW-T MINI. CIRCUIT BREAKER
Rated Current (A)	6
Rated Voltage (V)	415
Current Type	AC
Number of Poles	2
Instantaneous Tripping	TYPE C
Breaking Capacity at 415V (kA)	10
Cycles with Rated Current	4000
Cycles without Rated Current	4000
Compliant with Standard(s)	IEC 60898-1

Product Dimensions & Weight

Width (mm)	36
Height (mm)	92,6
Depth (mm)	73,5
Weight (kg)	0,26

Logistic Dimensions & Gross Weight

Length (cm)	9,5
Width (cm)	3,5
Height (cm)	7,5
Gross Weight (kg)	0,238
Volume (cdm)	0,249

Stock Data

Planned Delivery Time (Days)	79

Life Cycle

Sales Start	01.01.2016
Predecessor	247872 / BH-D10 2P 6A TYPE C N

Export Data

Legal Control (Dual Use List)	Not Listed
Country of Origin	India (IN)
Preference Status (Supplier Declaration)	Non EU

Environmental

REACH Limit Exceeded	NO
Dangerous Goods Class	NO
Dangerous Goods Identifier	NO
RoHS Compliance	COMPLIANT
WEEE	B2C

Conformity

CE	COMPLIANT

Documentation & Media Data

Manual URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=bltdae25c2bd5f2ff94&q=BHW-T10%202P%20Type%20C%206A&doc-lang=en
Certificates URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt8050dd1408c11cc2&q=BHW-T10%202P%20Type%20C%206A&doc-lang=en
CAD URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt26ecc97a31a841c1&q=BHW-T10%202P%20Type%20C%206A&doc-lang=en

Product Packaging

Cardboard (g)	12
Other paper (g)	0
Aluminum (g)	0
Steel (g)	0
Styrofoam (g)	0
Other plastic (g)	0
Wood (g)	0
Glass (g)	0
Others (g)	0

Compatible products

Material	Description / Price List Text / Classification
403893	AX-05BHW F Auxiliary switch-option for MCB; 1C 230VAC 5A; For 0.5 to 63A; Field fitted Class 100100801: FA-MCB: Miniature Circuit Breaker