



## MATERIAL FACT SHEET

### 247615 BV-D 4P 63A 300MA N

#### General Data

|                     |                                     |
|---------------------|-------------------------------------|
| Product Hierarchy   | IAN40101                            |
|                     | RCCB                                |
|                     | BV-D                                |
| Ext. Material Group | 10 STANDARD ITEM                    |
| ABC Indicator       | B (Limited Availability from Stock) |

e-shop: [https://mitsubishi-electric-eshop.mee.com/mee/FA\\_IA/EUR/en/p/000000000000247615](https://mitsubishi-electric-eshop.mee.com/mee/FA_IA/EUR/en/p/000000000000247615)

#### FA-MCB: Residual Current Circuit Breaker

|                                |                            |
|--------------------------------|----------------------------|
| Series                         | WS-V SERIES - RCCB         |
| Type                           | BV-D EARTH CIRCUIT BREAKER |
| Rated Current (A)              | 63                         |
| Rated Voltage (V)              | 230/400                    |
| Current Type                   | AC                         |
| Number of Poles                | 3+N                        |
| Breaking Capacity at 415V (kA) | 6                          |
| Cycles with Rated Current      | 8000                       |
| Cycles without Rated Current   | 8000                       |
| Rated Current Sensibility (mA) | 300                        |
| Pulsating Current Sensibility  | TYPE AC                    |

#### Product Dimensions & Weight

|             |      |
|-------------|------|
| Width (mm)  | 72   |
| Height (mm) | 85   |
| Depth (mm)  | 70   |
| Weight (kg) | 0,35 |

#### Logistic Dimensions & Gross Weight

|                   |       |
|-------------------|-------|
| Length (cm)       | 8,5   |
| Width (cm)        | 7,0   |
| Height (cm)       | 7,5   |
| Gross Weight (kg) | 0,342 |
| Volume (cdm)      | 0,446 |

#### Stock Data

|                              |    |
|------------------------------|----|
| Planned Delivery Time (Days) | 96 |
|------------------------------|----|

#### Life Cycle

|             |                                |
|-------------|--------------------------------|
| Sales Start | 05.03.2012                     |
| Predecessor | 135203 / BV-D 4P 63A 300MA(OS) |

#### Additional Product Information

|                  |    |
|------------------|----|
| Battery included | NO |
|------------------|----|

#### Export Data

|                                          |            |
|------------------------------------------|------------|
| Legal Control (Dual Use List)            | Not Listed |
| Country of Origin                        | China (CN) |
| Preference Status (Supplier Declaration) | Non EU     |

#### Environmental

|                            |           |
|----------------------------|-----------|
| REACH Limit Exceeded       | NO        |
| Dangerous Goods Class      | NO        |
| Dangerous Goods Identifier | NO        |
| RoHS Compliance            | COMPLIANT |
| WEEE                       | B2C       |

**Conformity**

|     |           |
|-----|-----------|
| CE  | COMPLIANT |
| EAC | COMPLIANT |

**Documentation & Media Data**

|                            |                                                                                                                                                                                                                                                                                                                           |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Manual URL Indicator       | <a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=BV-D%204P%2063A%20300MA%20N&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=BV-D%204P%2063A%20300MA%20N&amp;doc-lang=en</a> |
| Certificates URL Indicator | <a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=BV-D%204P%2063A%20300MA%20N&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=BV-D%204P%2063A%20300MA%20N&amp;doc-lang=en</a> |
| CAD URL Indicator          | <a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt26ecc97a31a841c1&amp;q=BV-D%204P%2063A%20300MA%20N&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt26ecc97a31a841c1&amp;q=BV-D%204P%2063A%20300MA%20N&amp;doc-lang=en</a> |

**Product Packaging**

|                   |       |
|-------------------|-------|
| Cardboard (g)     | 47,40 |
| Other paper (g)   | 0,11  |
| Aluminum (g)      | 0     |
| Steel (g)         | 0     |
| Styrofoam (g)     | 0,06  |
| Other plastic (g) | 0,06  |
| Wood (g)          | 8,89  |
| Glass (g)         | 0     |
| Others (g)        | 0     |