



MATERIAL FACT SHEET

599235 NV30-FAU 3P 20A 100-240V 30MA W

General Data

Product Hierarchy	IAN10203
	MCCB
	WS-V 1 - NV Body
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	C (Non-Stock Material / Make-to-Order)

e-shop: https://mitsubishi-electric-eshop.mee.com/mee/FA_IA/EUR/en/p/000000000000599235

FA-MCCB: Earth Leakage Circuit Breaker

Series	WS SERIES - ELCB
Type	NV-UL 489 LISTED
Frame Size	30
Rated Current (A)	20
Current Type	AC
Number of Poles	3
Rated Voltage (V)	100-240
Rated Current Sensibility (mA)	30
Max. Operating Time (s)	0,04
Compliant with Standard(s)	CSA C22.2 NO.5
Compliant with Standard(s) (2)	EN 60947-2
Compliant with Standard(s) (3)	IEC 60947-2
Compliant with Standard(s) (4)	UL 489
Automatic Tripping Device	THERMAL

Product Dimensions & Weight

Width (mm)	60
Height (mm)	72
Depth (mm)	73,5
Weight (kg)	0,22

Logistic Dimensions & Gross Weight

Length (cm)	8,0
Width (cm)	6,0
Height (cm)	9,0
Gross Weight (kg)	0,246
Volume (cdm)	0,432

Stock Data

Planned Delivery Time (Days)	104
------------------------------	-----

Life Cycle

Sales Start	02.06.2021
Predecessor	No Predecessor

Additional Product Information

Battery included	NO
------------------	----

Export Data

Legal Control (Dual Use List)	Not Listed
Country of Origin	Japan (JP)
Preference Status (Supplier Declaration)	Non EU

Environmental

Dangerous Goods Class	NO
Dangerous Goods Identifier	NO

RoHS Compliance	COMPLIANT
WEEE	B2C

Conformity

CE	COMPLIANT
UL/cUL	COMPLIANT
Shipping Approvals	NON-COMPLIANT
UKCA	COMPLIANT

Documentation & Media Data

Manual URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=bltdae25c2bd5f2ff94&q=Nv30-FAU%203P%2020A%20100-240V%2030MA%20W&doc-lang=en
----------------------	---