



MATERIAL FACT SHEET

721415 MCBT-B3/3

General Data

Product Hierarchy	IAN30111
	MCB
	E-MCBT
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	C (Non-Stock Material / Make-to-Order)

e-shop: <https://emea-fa.mitsubishielectric.com/fa/shop/material-page/00000000000721415>

FA-MDRC: MCB-T

Series	MODULAR DIN RAIL COMPONENTS
Type	MCBT (B-CURVE)
Rated Current (A)	3
Rated Voltage (V)	400
Current Type	AC
Number of Poles	3
Instantaneous Tripping	TYPE B
Breaking Capacity at 415V (kA)	IEC 60898: 10kA
Breaking Capacity at 415V (kA) (2)	IEC 60947-2: 10kA
Compliant with Standard(s)	CSA-C22.2
Compliant with Standard(s) (2)	EN 45545-2
Compliant with Standard(s) (3)	IEC 61373
Compliant with Standard(s) (4)	IEC/EN 60898
Compliant with Standard(s) (5)	IEC/EN 60947-2

Logistic Dimensions & Gross Weight

Length (cm)	8,0
Width (cm)	5,4
Height (cm)	7,6
Gross Weight (kg)	0,358
Volume (cdm)	0,326

Stock Data

Planned Delivery Time (Days)	45
------------------------------	----

Life Cycle

Sales Start	01.09.2024
Predecessor	No Predecessor

Additional Product Information

Battery included	NO
------------------	----

Export Data

Commodity Code	85362010
Legal Control (Dual Use List)	Not Listed
Country of Origin	Romania (RO)
Preference Status (Supplier Declaration)	Non EU

Environmental

REACH Limit Exceeded	YES
REACH Substance CAS Number	7439-92-1
Dangerous Goods Class	NO
Dangerous Goods Identifier	NO
RoHS Compliance	COMPLIANT
WEEE	B2B

Conformity

CE	COMPLIANT
EAC	NON-COMPLIANT

Documentation & Media Data

Manual URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=bltdae25c2bd5f2ff94&q=MCBT-B3/3&doc-lang=en
Certificates URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt8050dd1408c11cc2&q=MCBT-B3/3&doc-lang=en
CAD URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt26ecc97a31a841c1&q=MCBT-B3/3&doc-lang=en