



MATERIAL FACT SHEET

59393 TH-N20TACXKP 22A

General Data

Product Hierarchy	IAN50107
	MC
	TH-N Body
Ext. Material Group	10 DISCONTINUED
ABC Indicator	C (Non-Stock Material / Make-to-Order)

e-shop: https://mitsubishi-electric-eshop.mee.com/mee/FA_IA/EUR/en/p/000000000000059393

FA-MC: Overload Protection Relays

Series	MS-N THERMAL OVERLOAD RELAY
Type	WITH 3-ELEMENT (2E)
Heater Designation (A)	22
Range of Setting Current (A)	18 - 26
Rated Capacity (kW)	3-PHASE 220-240V: 5,5
Rated Capacity (kW) (2)	3-PHASE 380-440V: 11
Rated Voltage (V)	690
Frequency Range (Hz)	0(DC) - 400
Min. Ambient Temperature (°C)	-10
Max. Ambient Temperature (°C)	+40
No of Auxiliary Contacts NO	1
No of Auxiliary Contacts NC	1

Product Dimensions & Weight

Width (mm)	74
Height (mm)	72
Depth (mm)	83,5
Weight (kg)	0,2

Logistic Dimensions & Gross Weight

Length (cm)	8,0
Width (cm)	8,0
Height (cm)	10,0
Gross Weight (kg)	0,240
Volume (cdm)	0,640

Stock Data

Planned Delivery Time (Days)	254
------------------------------	-----

Life Cycle

Sales Start	20.10.1998
Predecessor	No Predecessor

Additional Product Information

Battery included	NO
------------------	----

Export Data

Legal Control (Dual Use List)	Not Listed
Country of Origin	Japan (JP)
Preference Status (Supplier Declaration)	Non EU

Environmental

REACH Limit Exceeded	NO
Dangerous Goods Class	NO
Dangerous Goods Identifier	NO
RoHS Compliance	COMPLIANT

WEEE	B2B
------	-----

Conformity

CE	COMPLIANT
----	-----------

Documentation & Media Data

Manual URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=bltdae25c2bd5f2ff94&q=TH-N20TACXKP%2022A&doc-lang=en
----------------------	---

Product Packaging

Cardboard (g)	100
Other paper (g)	10
Aluminum (g)	0
Steel (g)	0
Styrofoam (g)	0
Other plastic (g)	0
Wood (g)	0
Glass (g)	0
Others (g)	0