



MATERIAL FACT SHEET

505782 NZ2GNCF1-32T(C)

General Data

Product Hierarchy	IAD50305
	Modular PLC
	CC-LINK
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	C (Non-Stock Material / Make-to-Order)

e-shop: https://mitsubishi-electric-eshop.mee.com/mee/FA_IA/EUR/en/p/000000000000505782

FA-MOD PLC: Digital Output Module

Series	CC-LINK IE TSN
Type	REMOTE TRANSISTOR OUTPUT
Power Supply (V)	24
Current Type	DC
Occupied Stations	1
Integrated Digital Outputs	32
Output Type	TRANSISTOR
Output Logic	SINK
Rated Load Voltage (VDC)	12/24
Wiring	CONNECTOR
Int. Current Consumption (A)	0,12

Product Dimensions & Weight

Width (mm)	179
Height (mm)	54,5
Depth (mm)	35,5
Weight (kg)	0,16

Logistic Dimensions & Gross Weight

Length (cm)	25,0
Width (cm)	9,0
Height (cm)	8,0
Gross Weight (kg)	0,290
Volume (cdm)	1,800

Stock Data

Planned Delivery Time (Days)	136
------------------------------	-----

Life Cycle

Sales Start	18.06.2020
Predecessor	No Predecessor

Additional Product Information

Difference to Standard 1	COATING
Battery included	NO

Export Data

Legal Control (Dual Use List)	Not Listed
Country of Origin	Japan (JP)
Preference Status (Supplier Declaration)	Non EU

Environmental

Dangerous Goods Class	NO
Dangerous Goods Identifier	NO
RoHS Compliance	COMPLIANT
WEEE	B2B

Conformity

CE	COMPLIANT
UL/cUL	COMPLIANT
EAC	COMPLIANT
UKCA	COMPLIANT

Documentation & Media Data

Manual URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=bltdae25c2bd5f2ff94&q=NZ2GNCF1-32T(C)&doc-lang=en
Certificates URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt8050dd1408c11cc2&q=NZ2GNCF1-32T(C)&doc-lang=en
CAD URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt26ecc97a31a841c1&q=NZ2GNCF1-32T(C)&doc-lang=en
Network configuration file URL	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blte8cf990c7c524b4e&q=NZ2GNCF1-32T(C)&doc-lang=en

Product Packaging

Cardboard (g)	110
Other paper (g)	0
Aluminum (g)	0
Steel (g)	0
Styrofoam (g)	0
Other plastic (g)	4
Wood (g)	0
Glass (g)	0
Others (g)	0

Compatible products

Material	Description / Price List Text / Classification
134139	A6CON1 PLC Connection-plug for I/O-Modules Source-Input/Sink-Output, soldering Class 100100215: FA-MOD PLC: Other Option
134140	A6CON2 PLC Connection-plug for I/O-Modules Source-Input/Sink-Output, crimp Class 100100215: FA-MOD PLC: Other Option
134141	A6CON3 PLC Connection-plug for I/O-Modules Source-Input/Sink-Output, wrap Class 100100215: FA-MOD PLC: Other Option
140991	Q40CBL-3M PLC Connection cable 40-pin modules (A6CON-type), shielded, length 3 m, open end Class 100100214: FA-MOD PLC: Cable
140997	Q40CBL-5M PLC Connection cable 40-pin modules (A6CON-type), shielded, length 5 m open end Class 100100214: FA-MOD PLC: Cable
146923	A6CON4 PLC Connection-plug for I/O-Modules as A6CON-1 w/ 45 degree cable-outlet Class 100100215: FA-MOD PLC: Other Option
158068	Q40CBL-10M PLC Connection cable 40-pin modules (A6CON-type), shielded, length 10 m open end Class 100100214: FA-MOD PLC: Cable
158069	Q40CBL-15M PLC Connection cable 40-pin modules (A6CON-type), shielded, length 15 m open end Class 100100214: FA-MOD PLC: Cable
278166	SC-E5EW-S45M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor;45m Class 100100214: FA-MOD PLC: Cable
291807	SC-E5EW-S1M-MV Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor; 1m Class 100100214: FA-MOD PLC: Cable
291808	SC-E5EW-S3M-MV Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor; 3m Class 100100214: FA-MOD PLC: Cable
295425	SC-E5EW-S05M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight;indoor;0.5m Class 100100214: FA-MOD PLC: Cable
295426	SC-E5EW-S1M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor; 1m Class 100100214: FA-MOD PLC: Cable

Material	Description / Price List Text / Classification
295427	SC-E5EW-S3M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor; 2m Class 100100214: FA-MOD PLC: Cable
314841	Q40CBL-10M-S PLC Connection cable 40-pin modules(A6CON-type),10m,open,LiYY 40x0,14 mm²,flex Class 100100214: FA-MOD PLC: Cable
314842	Q40CBL-15M-S PLC Connection cable 40-pin modules(A6CON-type),15m open,LiYY 40x0,14 mm²,flex Class 100100214: FA-MOD PLC: Cable
413182	SC-E5EW-S10M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor;10m Class 100100214: FA-MOD PLC: Cable
413183	SC-E5EW-S25M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor;25m Class 100100214: FA-MOD PLC: Cable
413184	SC-E5EW-S5M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor; 5m Class 100100214: FA-MOD PLC: Cable
486376	SC-E5EW-S2M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor; 2m Class 100100214: FA-MOD PLC: Cable
486377	SC-E5EW-S4M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor; 4m Class 100100214: FA-MOD PLC: Cable
487403	SC-E5EW-S15M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor;15m Class 100100214: FA-MOD PLC: Cable
487404	SC-E5EW-S20M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor;20m Class 100100214: FA-MOD PLC: Cable
557483	SC-E5EW-S100M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight;indoor;100m Class 100100214: FA-MOD PLC: Cable