



MATERIAL FACT SHEET

221863 AJ65SBT2B-64DA

General Data

Product Hierarchy	IAD50501
	Modular PLC
	A2C-PLC
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	B (Limited Availability from Stock)

e-shop: https://mitsubishi-electric-eshop.mee.com/mee/FA_IA/EUR/en/p/000000000000221863

FA-MOD PLC: Analogue I/O Module

Series	CC-LINK
Type	REMOTE ANALOG OUTPUT
Power Supply (V)	24
Current Type	DC
Occupied I/O Points on PLC	32
Occupied Stations	1
Integrated Analogue Outputs	4
Output Voltage Range (V)	-10-10
Output Current Range (mA)	0-20
Wiring	SCREW
Int. Current Consumption (A)	0,24

Product Dimensions & Weight

Width (mm)	122
Height (mm)	50
Depth (mm)	54
Weight (kg)	0,25

Logistic Dimensions & Gross Weight

Length (cm)	13,8
Width (cm)	8,5
Height (cm)	10,5
Gross Weight (kg)	0,344
Volume (cdm)	1,232

Stock Data

Planned Delivery Time (Days)	136
------------------------------	-----

Life Cycle

Sales Start	11.05.2009
Predecessor	75446 / AJ65BT-64DAV

Additional Product Information

Binding Tariff Information	DEBTI-10685/21-1
BTI validity date	31.10.2024
Battery included	NO

Export Data

Legal Control (Dual Use List)	Not Listed
Country of Origin	Japan (JP)
Preference Status (Supplier Declaration)	Non EU

Environmental

REACH Limit Exceeded	YES
REACH Substance CAS Number	13560-89-9
REACH Substance CAS Number (2)	7439-92-1

REACH Substance CAS Number (3)	80-05-7
Dangerous Goods Class	NO
Dangerous Goods Identifier	NO
RoHS Compliance	COMPLIANT
WEEE	B2B

Conformity

CE	COMPLIANT
UL/cUL	COMPLIANT
EAC	COMPLIANT
UKCA	COMPLIANT

Documentation & Media Data

Manual URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=bltdae25c2bd5f2ff94&q=AJ65SBT2B-64DA&doc-lang=en
Certificates URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt8050dd1408c11cc2&q=AJ65SBT2B-64DA&doc-lang=en
Network configuration file URL	X

Product Packaging

Cardboard (g)	80
Other paper (g)	1
Aluminum (g)	0
Steel (g)	0
Styrofoam (g)	0
Other plastic (g)	5
Wood (g)	0
Glass (g)	0
Others (g)	0