



MATERIAL FACT SHEET

163966 AJ65SBTB1-16T1

General Data

Product Hierarchy	IAD50501
	Modular PLC
	A2C-PLC
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	C (Non-Stock Material / Make-to-Order)

e-shop: https://mitsubishi-electric-eshop.mee.com/mee/FA_1A/EUR/en/p/000000000000163966

FA-MOD PLC: Digital Output Module

Series	CC-LINK
Type	REMOTE TRANSISTOR OUTPUT
Power Supply (V)	24
Current Type	DC
Occupied Stations	1
Integrated Digital Outputs	16
Output Type	TRANSISTOR
Output Logic	SINK
Rated Load Voltage (VDC)	12/24
Wiring	SCREW
Int. Current Consumption (A)	0,05

Product Dimensions & Weight

Width (mm)	228
Height (mm)	50
Depth (mm)	40
Weight (kg)	0,18

Logistic Dimensions & Gross Weight

Length (cm)	25,0
Width (cm)	8,0
Height (cm)	9,0
Gross Weight (kg)	0,254
Volume (cdm)	1,800

Stock Data

Planned Delivery Time (Days)	75
------------------------------	----

Life Cycle

Sales Start	04.08.2005
Predecessor	75449 / AJ65BTB1-16T

Additional Product Information

Battery included	NO
------------------	----

Export Data

Legal Control (Dual Use List)	Not Listed
Country of Origin	Japan (JP)
Preference Status (Supplier Declaration)	Non EU

Environmental

REACH Limit Exceeded	YES
REACH Substance CAS Number	2451-62-9
REACH Substance CAS Number (2)	7439-92-1
Dangerous Goods Class	NO
Dangerous Goods Identifier	NO

RoHS Compliance	COMPLIANT
WEEE	B2B

Conformity

CE	COMPLIANT
UL/cUL	COMPLIANT
EAC	COMPLIANT
UKCA	COMPLIANT

Documentation & Media Data

Manual URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=bltdae25c2bd5f2ff94&q=AJ65SBTB1-16T1&doc-lang=en
Certificates URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt8050dd1408c11cc2&q=AJ65SBTB1-16T1&doc-lang=en
CAD URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt26ecc97a31a841c1&q=AJ65SBTB1-16T1&doc-lang=en

Product Packaging

Cardboard (g)	33
Other paper (g)	9
Aluminum (g)	0
Steel (g)	0
Styrofoam (g)	0
Other plastic (g)	3
Wood (g)	0
Glass (g)	0
Others (g)	0