



MATERIAL FACT SHEET

149501 QJ71C24N-R2

General Data

Product Hierarchy	IAD50702
	Modular PLC
	Q-Single
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	A (Available from Stock)

e-shop: https://mitsubishi-electric-eshop.mee.com/mee/FA_IA/EUR/en/p/0000000000000149501

FA-MOD PLC: Serial Com Module

Series	MELSEC-Q SERIES
Interface	RS-232

Product Dimensions & Weight

Width (mm)	27,4
Height (mm)	98
Depth (mm)	90
Weight (kg)	0,135

Logistic Dimensions & Gross Weight

Length (cm)	14,0
Width (cm)	12,0
Height (cm)	5,0
Gross Weight (kg)	0,150
Volume (cdm)	0,840

Stock Data

Planned Delivery Time (Days)	75
------------------------------	----

Life Cycle

Sales Start	19.05.2003
Predecessor	136384 / QD51

Additional Product Information

Binding Tariff Information	DEBTI-10913/21-1
BTI validity date	04.08.2024
Battery included	NO

Export Data

Legal Control (Dual Use List)	Not Listed
Country of Origin	Japan (JP)
Preference Status (Supplier Declaration)	Non EU

Environmental

REACH Limit Exceeded	YES
REACH Substance CAS Number	12060-00-3
REACH Substance CAS Number (2)	1303-86-2
REACH Substance CAS Number (3)	1317-36-8
Dangerous Goods Class	NO
Dangerous Goods Identifier	NO
RoHS Compliance	COMPLIANT
WEEE	B2B

Conformity

CE	COMPLIANT
UL/cUL	COMPLIANT

EAC	COMPLIANT
Shipping Approvals	ABS,BV,DNV GL,LR,NK,RINA
UKCA	COMPLIANT

Documentation & Media Data

Manual URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=bltdae25c2bd5f2ff94&q=QJ71C24N-R2&doc-lang=en
Certificates URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt8050dd1408c11cc2&q=QJ71C24N-R2&doc-lang=en
CAD URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt26ecc97a31a841c1&q=QJ71C24N-R2&doc-lang=en

Product Packaging

Cardboard (g)	70
Other paper (g)	11
Aluminum (g)	0
Steel (g)	0
Styrofoam (g)	0
Other plastic (g)	2
Wood (g)	0
Glass (g)	0
Others (g)	0

Compatible products

Material	Description / Price List Text / Classification
502144	17JE-23090-02(D8A)(-CG) Connector; RS-232 D-sub 9 pin; male; M2.6 screw; cable diameter max 7,5 mm Class 100100215: FA-MOD PLC: Other Option