



MATERIAL FACT SHEET

247619 BV-D 4P 25A 300MA N

General Data

Product Hierarchy	IAN40101
	RCCB
	BV-D
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	B (Limited Availability from Stock)

e-shop: https://mitsubishi-electric-eshop.mee.com/mee/FA_IA/EUR/en/p/000000000000247619

FA-MCB: Residual Current Circuit Breaker

Series	WS-V SERIES - RCCB
Type	BV-D EARTH CIRCUIT BREAKER
Rated Current (A)	25
Rated Voltage (V)	230/400
Current Type	AC
Number of Poles	3+N
Breaking Capacity at 415V (kA)	6
Cycles with Rated Current	8000
Cycles without Rated Current	8000
Rated Current Sensibility (mA)	300
Pulsating Current Sensibility	TYPE AC

Product Dimensions & Weight

Width (mm)	72
Height (mm)	85
Depth (mm)	70
Weight (kg)	0,35

Logistic Dimensions & Gross Weight

Length (cm)	8,7
Width (cm)	7,3
Height (cm)	7,5
Gross Weight (kg)	0,344
Volume (cdm)	0,476

Stock Data

Planned Delivery Time (Days)	96
------------------------------	----

Life Cycle

Sales Start	05.03.2012
Predecessor	135191 / BV-D 4P 25A 300MA(OS)

Additional Product Information

Battery included	NO
------------------	----

Export Data

Legal Control (Dual Use List)	Not Listed
Country of Origin	China (CN)
Preference Status (Supplier Declaration)	Non EU

Environmental

REACH Limit Exceeded	NO
Dangerous Goods Class	NO
Dangerous Goods Identifier	NO
RoHS Compliance	COMPLIANT
WEEE	B2C

Conformity

CE	COMPLIANT
EAC	COMPLIANT

Documentation & Media Data

Manual URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=bltdae25c2bd5f2ff94&q=BV-D%204P%2025A%20300MA%20N&doc-lang=en
Certificates URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt8050dd1408c11cc2&q=BV-D%204P%2025A%20300MA%20N&doc-lang=en
CAD URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt26ecc97a31a841c1&q=BV-D%204P%2025A%20300MA%20N&doc-lang=en

Product Packaging

Cardboard (g)	47,40
Other paper (g)	0,11
Aluminum (g)	0
Steel (g)	0
Styrofoam (g)	0,06
Other plastic (g)	0,06
Wood (g)	8,89
Glass (g)	0
Others (g)	0