



MATERIAL FACT SHEET

265626 NV125-CV 3P 125A 2-440V 1.2.500MA JIEN C

General Data

Product Hierarchy	IAN10203
	MCCB
	WS-V 1 - NV Body
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	B (Limited Availability from Stock)

e-shop: https://mitsubishi-electric-eshop.mee.com/mee/FA_IA/EUR/en/p/000000000000265626

FA-MCCB: Earth Leakage Circuit Breaker

Series	WS-V SERIES - ELCB
Type	NV-C TYPE (ECONOMY CLASS)
Frame Size	125
Rated Current (A)	125
Current Type	AC
Number of Poles	3
Rated Voltage (V)	2-440
Rated Current Sensibility (mA)	100/200/500
Max. Operating Time (s)	0,04
Pulsating Current Sensibility	A (HARMONIC SURGE READY)
Breaking Capacity at 400V (kA)	10/5
Compliant with Standard(s)	EN 60947-2
Compliant with Standard(s) (2)	IEC 60947-2
Cycles with Rated Current	6000
Cycles without Rated Current	10000
Automatic Tripping Device	THERMAL-MAGNETIC

Product Dimensions & Weight

Width (mm)	90
Height (mm)	130
Depth (mm)	90
Weight (kg)	1

Logistic Dimensions & Gross Weight

Length (cm)	13,0
Width (cm)	10,0
Height (cm)	9,5
Gross Weight (kg)	0,971
Volume (cdm)	1,235

Stock Data

Planned Delivery Time (Days)	104
------------------------------	-----

Life Cycle

Sales Start	18.07.2013
Predecessor	No Predecessor

Additional Product Information

Battery included	NO
------------------	----

Export Data

Legal Control (Dual Use List)	Not Listed
Country of Origin	Japan (JP)
Preference Status (Supplier Declaration)	Non EU

Environmental

REACH Limit Exceeded	NO
Dangerous Goods Class	NO
Dangerous Goods Identifier	NO
RoHS Compliance	COMPLIANT
WEEE	B2C

Conformity

CE	COMPLIANT
UL/cUL	NON-COMPLIANT
Shipping Approvals	NON-COMPLIANT
UKCA	COMPLIANT

Documentation & Media Data

Manual URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=bltdae25c2bd5f2ff94&q=NV125-CV%203P%20125A%202-440V%201.2.500MA%20J1EN%20C&doc-lang=en
Certificates URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt8050dd1408c11cc2&q=NV125-CV%203P%20125A%202-440V%201.2.500MA%20J1EN%20C&doc-lang=en
CAD URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt26ecc97a31a841c1&q=NV125-CV%203P%20125A%202-440V%201.2.500MA%20J1EN%20C&doc-lang=en

Product Packaging

Cardboard (g)	69
Other paper (g)	0
Aluminum (g)	0
Steel (g)	0
Styrofoam (g)	0
Other plastic (g)	0
Wood (g)	0
Glass (g)	0
Others (g)	0