



MATERIAL FACT SHEET

283529 FX5UC-32MT/D

General Data

Product Hierarchy	IAD21701
	Compact PLC
	FX5U CPU
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	C (Non-Stock Material / Make-to-Order)

e-shop: https://mitsubishi-electric-eshop.mee.com/mee/FA_I/A/EUR/en/p/000000000000283529

FA-COM PLC: Main Unit

Series	MELSEC IQ-F SERIES
Type	FX5UC
Power Supply (V)	24
Current Type	DC
Program Memory	64K STEPS
Program Memory Unit	FLASH
Integrated Digital Inputs	16
Integrated Digital Outputs	16
Output Type	TRANSISTOR
Output Logic	SINK
Local I/O Points	256
Local + Remote I/O Points	512
Expandable	YES
Cycle Time LD (ns)	34
Cycle Time MOV (ns)	34
Ethernet Port	1
RS-485	1
Power Consumption (W)	5
Buffer Battery	OPTION
Protection Class	IP10
Min. Ambient Temperature (°C)	0
Max. Ambient Temperature (°C)	55

Product Dimensions & Weight

Width (mm)	42,1
Height (mm)	90
Depth (mm)	89,1
Weight (kg)	0,2

Logistic Dimensions & Gross Weight

Length (cm)	14,0
Width (cm)	11,5
Height (cm)	10,0
Gross Weight (kg)	0,301
Volume (cdm)	1,610

Stock Data

Planned Delivery Time (Days)	58
------------------------------	----

Life Cycle

Sales Start	23.02.2015
Predecessor	No Predecessor

Additional Product Information

Binding Tariff Information	DEBTI-10856/21-1
BTI validity date	10.10.2024
Battery included	NO

Export Data

Legal Control (Dual Use List)	Not Listed
Country of Origin	Japan (JP)
Preference Status (Supplier Declaration)	Non EU

Environmental

REACH Limit Exceeded	NO
Dangerous Goods Class	NO
Dangerous Goods Identifier	NO
RoHS Compliance	COMPLIANT
WEEE	B2B

Conformity

CE	COMPLIANT
UL/cUL	COMPLIANT
EAC	COMPLIANT
Shipping Approvals	ABS,BV,DNV GL,KR,LR,NK,RINA
UKCA	COMPLIANT

Documentation & Media Data

Manual URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=bltdae25c2bd5f2ff94&q=FX5UC-32MT/D&doc-lang=en
Certificates URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt8050dd1408c11cc2&q=FX5UC-32MT/D&doc-lang=en
CAD URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt26ecc97a31a841c1&q=FX5UC-32MT/D&doc-lang=en

Product Packaging

Cardboard (g)	75
Other paper (g)	0
Aluminum (g)	0
Steel (g)	0
Styrofoam (g)	0
Other plastic (g)	0
Wood (g)	0
Glass (g)	0
Others (g)	0

Spare parts

Material	Description	Quantity	Unit
302400	FX5U-32/64/80Mx /ES/ESS COVER CONNECTOR	1	PC
334390	FX5UC-32MT/D COVER MAIN	1	PC
334392	FX5UC-32MT/D/DSS COVER TOP	1	PC
334393	FX5UC-32MT/D/DSS COVER EXTENSION	1	PC
334394	FX5UC-32MT/D/DSS COVER BATTERY	1	PC
334405	FX5UC-32MT/D/DSS COVER BOTTOM	1	PC
334406	FX5UC-32MT/D PCB I/O	1	PC
334408	FX5UC-32MT/D PCB POWER	1	PC

Compatible products

Material	Description / Price List Text / Classification
104509	FX2NC-100MPCB PLC, FX Series Power supply cable for FX2NC base unit, 1 m Class 100100110: FA-COM PLC: Cable
104510	FX2NC-100BPCB Cable for 24V DC supply to input units Class 100100110: FA-COM PLC: Cable
104511	FX2NC-10BPCB1 Crossover cable for input units Class 100100110: FA-COM PLC: Cable
125189	FX-16E-TB/UL PLC, FX Series Extension terminal block 16 inputs/outputs Class 100100111: FA-COM PLC: Other Option
125584	FX-16E-150CAB PLC, FX Series Connecting cable 1,5 m FX2N-XXGM > terminal block Class 100100110: FA-COM PLC: Cable
128722	FX-16E-300CAB PLC, FX Series Connecting cable 3 m FX2N-XXGM > terminal block Class 100100110: FA-COM PLC: Cable

Material	Description / Price List Text / Classification
128723	FX-16E-500CAB-S PLC, FX Series Connecting cable 5 m FX2N-XXGM > External devices Class 100100110: FA-COM PLC: Cable
128724	FX-32E-TB/UL PLC, FX Series Extension terminal block 32 inputs/outputs Class 100100111: FA-COM PLC: Other Option
130451	FX-16E-500CAB PLC, FX Series Connecting cable 5 m FX2N-XXGM > terminal block Class 100100110: FA-COM PLC: Cable
134236	FX-16E-150CAB-R PLC, FX Series Extension terminal block cable, 1,5 m Class 100100110: FA-COM PLC: Cable
134265	FX-16E-300CAB-R PLC, FX Series Extension terminal block cable, 3 m Class 100100110: FA-COM PLC: Cable
134270	FX-16E-500CAB-R PLC, FX Series Extension terminal block cable, 5 m Class 100100110: FA-COM PLC: Cable
149021	TB-16EX-S PLC, FX Series Sensor terminal block for 16 inputs, screw connection Class 100100111: FA-COM PLC: Other Option
149038	TB-EX-CAB-1M PLC, FX Series Connection cable 1 m for terminal block TB-EX / TB-20 Class 100100110: FA-COM PLC: Cable
149039	TB-EX-CAB-3M PLC, FX Series Connection cable 3 m for terminal block TB-EX / TB-20 Class 100100110: FA-COM PLC: Cable
149040	TB-EX-CAB-5M PLC, FX Series Connection cable 5 m for terminal block TB-EX / TB-20 Class 100100110: FA-COM PLC: Cable
149148	TB-20-S PLC, FX Series Terminal block, 20 pin., screw connection Class 100100111: FA-COM PLC: Other Option
165286	FX3U-32BL PLC, FX3U/C Battery Class 100100112: FA-COM PLC: Spare Part
165286	FX3U-32BL PLC, FX3U/C Battery Class 100101303: FA-OTHERS: Battery
278166	SC-E5EW-S45M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor;45m Class 100100214: FA-MOD PLC: Cable
280510	FX5-CNV-BUS FX5;FX3 Bus Conversion Unit Class 100100111: FA-COM PLC: Other Option
283557	FX5-CNV-IFC FX5UC;FX5U Bus Converter Class 100100111: FA-COM PLC: Other Option
283558	FX5-CNV-BUSC FX5UC;FX3 Bus Conversion Unit Class 100100111: FA-COM PLC: Other Option
284378	GX Works3 V01-2L0C-E PLC Programming-S/W for Melsec iQ-R/iQ- F;engl;USB;2 PC's Class 100101201: FA-Software: Software PLC
284379	GX Works3 V01-5L0C-E PLC Programming-S/W for Melsec iQ-R/iQ- F; engl; USB; 5 PC's Class 100101201: FA-Software: Software PLC
284966	NZ1MEM-2GBSD SD Memory Card; 2 GByte Class 100100215: FA-MOD PLC: Other Option
284967	NZ1MEM-4GBSD SD Memory Card; 4 GByte Class 100100215: FA-MOD PLC: Other Option
284968	NZ1MEM-8GBSD SD Memory Card; 8 GByte Class 100100215: FA-MOD PLC: Other Option
284969	NZ1MEM-16GBSD SD Memory Card; 16 GByte Class 100100215: FA-MOD PLC: Other Option

Material	Description / Price List Text / Classification
286227	iQ Works V02-2L0C-E iQ Works V2.0;incl Navigator,GX Works,GT Works,MT Works;engl;USB;2 PC´s Class 100101201: FA-Software: Software PLC
286228	iQ Works V02-5L0C-E iQ Works V2.0;incl Navigator,GX Works,GT Works,MT Works;engl;USB;5 PC´s Class 100101201: FA-Software: Software PLC
291807	SC-E5EW-S1M-MV Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor; 1m Class 100100214: FA-MOD PLC: Cable
291808	SC-E5EW-S3M-MV Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor; 3m Class 100100214: FA-MOD PLC: Cable
294586	FX5-C1PS-5V FX5UC;Power Supply Unit 5VDC Bus Class 100100111: FA-COM PLC: Other Option
295425	SC-E5EW-S05M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight;indoor;0.5m Class 100100214: FA-MOD PLC: Cable
295426	SC-E5EW-S1M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor; 1m Class 100100214: FA-MOD PLC: Cable
295427	SC-E5EW-S3M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor; 2m Class 100100214: FA-MOD PLC: Cable
297456	FX5-CNV-BC FX5;Bus Extension cable connector Class 100100111: FA-COM PLC: Other Option
297457	FX5-30EC FX5;Bus Extension cable (0,3m) Class 100100110: FA-COM PLC: Cable
297458	FX5-65EC FX5;Bus Extension cable (0,65m) Class 100100110: FA-COM PLC: Cable
303426	iQ Works V02-15L0C-E iQ Works V2.0;incl Navigator,GX Works,GT Works,MT Works;engl;USB;15 PC´s Class 100101201: FA-Software: Software PLC
304614	GX Works3 V01-2L0C-G PLC Programming SW; Melsec iQ-R/iQ- F only (no GXW2/GX Dev); USB; 2 PCs; German Class 100101201: FA-Software: Software PLC
304645	GX Works3 V01-5L0C-G PLC Programming SW; Melsec iQ-R/iQ- F only (no GXW2/GX Dev); USB; 5 PCs; German Class 100101201: FA-Software: Software PLC
308856	GX Works3 V01-2L0C-IT PLC Programming-S/W for Melsec iQ-R/iQ- F;engl;USB;2 PC´s; Italian Class 100101201: FA-Software: Software PLC
338821	iQ Works V02-2L0C-G iQ Works V2.0;incl Navigator,GX Works,GT Works,MT Works;German;USB;2 PC´s Class 100101201: FA-Software: Software PLC
339022	iQ Works V02-5L0C-G iQ Works V2.0;incl Navigator,GX Works,GT Works,MT Works;German;USB;5 PC´s Class 100101201: FA-Software: Software PLC
340984	Transcend SDHC card 16GB Class 10 SDHC memory card 16GB; Class 10; R: 30MB/s; W: 15MB/s Class 100100304: FA-HMI: Other Option
401853	iQ Works V02-2L0C-IT iQ Works V2.0;incl Navigator,GX Works,GT Works,MT Works;Italian;USB;2 PCs Class 100101201: FA-Software: Software PLC
413182	SC-E5EW-S10M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor;10m Class 100100214: FA-MOD PLC: Cable
413183	SC-E5EW-S25M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor;25m Class 100100214: FA-MOD PLC: Cable
413184	SC-E5EW-S5M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor; 5m Class 100100214: FA-MOD PLC: Cable
413493	TRIO-PS-2G/1AC/24DC/5 Power supply unit for 100-240V AC; Output 24V DC / 5A, DIN rail mounting Class 100100304: FA-HMI: Other Option

Material	Description / Price List Text / Classification
414700	TRIO-PS-2G/1AC/24DC/3/C2LPS Power supply unit for 100-240V AC; Output 24V DC / 3A C2LPS, DIN rail mounting Class 100100304: FA-HMI: Other Option
486376	SC-E5EW-S2M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor; 2m Class 100100214: FA-MOD PLC: Cable
486377	SC-E5EW-S4M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor; 4m Class 100100214: FA-MOD PLC: Cable
487403	SC-E5EW-S15M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor;15m Class 100100214: FA-MOD PLC: Cable
487404	SC-E5EW-S20M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor;20m Class 100100214: FA-MOD PLC: Cable
491761	Verbatim microSDHC Card 16GB Class 10 MicroSDHC memory card 16GB; Class 10; R/W: 10MB/s; adapter included Class 100100215: FA-MOD PLC: Other Option
506252	TRIO-PS-2G/1AC/24DC/10 Primary switched power supply; input: single phase, output: 24 VDC/10A, DIN rail Class 100100304: FA-HMI: Other Option
506253	TRIO-PS-2G/1AC/24DC/20 Primary switched power supply; input: single phase, output: 24 VDC/20A, DIN rail Class 100100304: FA-HMI: Other Option
506254	TRIO-PS-2G/3AC/24DC/20 Primary switched power supply; input: 3-phase, output: 24 VDC/20A, DIN rail Class 100100304: FA-HMI: Other Option
506255	TRIO-PS-2G/3AC/24DC/40 Primary switched power supply; input: 3-phase, output: 24 VDC/40A, DIN rail Class 100100304: FA-HMI: Other Option
557483	SC-E5EW-S100M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight;indoor;100m Class 100100214: FA-MOD PLC: Cable
612154	FX5-CNV-BUS-BS FX5;FX3 Bus Conversion Unit; coated Class 100100111: FA-COM PLC: Other Option
612156	FX5-CNV-IFC-BS FX5UC;FX5U Bus Converter; coated Class 100100111: FA-COM PLC: Other Option
612268	Transcend SDHC Card 8GB Class 4 SDHC memory card 8GB; Class 4; R: 18MB/s; W: 6MB/s Class 100100304: FA-HMI: Other Option