



MATERIAL FACT SHEET

307562 RD40PD01

General Data

Product Hierarchy	IAD51401
	Modular PLC
	IQ-R Standard
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	B (Limited Availability from Stock)

e-shop: https://mitsubishi-electric-eshop.mee.com/mee/FA_1A/EUR/en/p/000000000000307562

FA-MOD PLC: Counter Module

Series	MELSEC IQ-R SERIES
Type	FLEXIBLE HIGH-SPEED I/O
Number of Channels	12
Int. Current Consumption (A)	0,76

Product Dimensions & Weight

Width (mm)	27,8
Height (mm)	106
Depth (mm)	110
Weight (kg)	0,16

Logistic Dimensions & Gross Weight

Length (cm)	16,0
Width (cm)	15,0
Height (cm)	5,0
Gross Weight (kg)	0,223
Volume (cdm)	1,200

Stock Data

Planned Delivery Time (Days)	75
------------------------------	----

Life Cycle

Sales Start	28.02.2017
Predecessor	No Predecessor

Additional Product Information

Battery included	NO
------------------	----

Export Data

Legal Control (Dual Use List)	Not Listed
Country of Origin	Japan (JP)
Preference Status (Supplier Declaration)	Non EU

Environmental

REACH Limit Exceeded	YES
REACH Substance CAS Number	7439-92-1
REACH Substance CAS Number (2)	80-05-7
REACH Substance CAS Number (3)	872-50-4
Dangerous Goods Class	NO
Dangerous Goods Identifier	NO
WEEE	B2B

Conformity

CE	COMPLIANT
UL/cUL	COMPLIANT
EAC	COMPLIANT

UKCA	COMPLIANT
------	-----------

Documentation & Media Data

Manual URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=bltdae25c2bd5f2ff94&q=RD40PD01&doc-lang=en
Certificates URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt8050dd1408c11cc2&q=RD40PD01&doc-lang=en

Product Packaging

Cardboard (g)	45
Other paper (g)	26
Aluminum (g)	0
Steel (g)	0
Styrofoam (g)	0
Other plastic (g)	3
Wood (g)	0
Glass (g)	0
Others (g)	0

Compatible products

Material	Description / Price List Text / Classification
134139	A6CON1 PLC Connection-plug for I/O-Modules Source-Input/Sink-Output, soldering Class 100100215: FA-MOD PLC: Other Option
134140	A6CON2 PLC Connection-plug for I/O-Modules Source-Input/Sink-Output, crimp Class 100100215: FA-MOD PLC: Other Option
140991	Q40CBL-3M PLC Connection cable 40-pin modules (A6CON-type), shielded, length 3 m, open end Class 100100214: FA-MOD PLC: Cable
140997	Q40CBL-5M PLC Connection cable 40-pin modules (A6CON-type), shielded, length 5 m open end Class 100100214: FA-MOD PLC: Cable
146923	A6CON4 PLC Connection-plug for I/O-Modules as A6CON-1 w/ 45 degree cable-outlet Class 100100215: FA-MOD PLC: Other Option
158068	Q40CBL-10M PLC Connection cable 40-pin modules (A6CON-type), shielded, length 10 m open end Class 100100214: FA-MOD PLC: Cable
158069	Q40CBL-15M PLC Connection cable 40-pin modules (A6CON-type), shielded, length 15 m open end Class 100100214: FA-MOD PLC: Cable
280077	FA-CBL20FV Connector digital IO conversion unit connection cable (DC); 40 core cable; 2.0m Class 100100214: FA-MOD PLC: Cable
280078	FA-CBL30FV Connector digital IO conversion unit connection cable (DC); 40 core cable; 3.0m Class 100100214: FA-MOD PLC: Cable
280079	FA-CBL50FV Connector digital IO conversion unit connection cable (DC); 40 core cable; 5.0m Class 100100214: FA-MOD PLC: Cable
280080	FA-CBL80FV Connector digital IO conversion unit connection cable (DC); 40 core cable;8.0m Class 100100214: FA-MOD PLC: Cable
314841	Q40CBL-10M-S PLC Connection cable 40-pin modules(A6CON-type),10m,open,LiYY 40x0,14 mm²,flex Class 100100214: FA-MOD PLC: Cable
314842	Q40CBL-15M-S PLC Connection cable 40-pin modules(A6CON-type),15m open,LiYY 40x0,14 mm²,flex Class 100100214: FA-MOD PLC: Cable