



MATERIAL FACT SHEET

221862 AJ65SBT2B-64RD3

General Data

Product Hierarchy	IAD50501
	Modular PLC
	A2C-PLC
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	C (Non-Stock Material / Make-to-Order)

e-shop: https://mitsubishi-electric-eshop.mee.com/mee/FA_IA/EUR/en/p/000000000000221862

FA-MOD PLC: Temperature Module

Series	CC-LINK
Type	TEMPERATURE INPUT
Power Supply (V)	24
Current Type	DC
Occupied Stations	1
Integrated Analogue Inputs	4
Input Type	RTD
Applicable RTD Type	JPT100
Applicable RTD Type (2)	NI100
Applicable RTD Type (3)	PT100
Int. Current Consumption (A)	0,14

Product Dimensions & Weight

Width (mm)	122
Height (mm)	50
Depth (mm)	54
Weight (kg)	0,25

Logistic Dimensions & Gross Weight

Length (cm)	13,5
Width (cm)	8,5
Height (cm)	10,0
Gross Weight (kg)	0,343
Volume (cdm)	1,148

Stock Data

Planned Delivery Time (Days)	136
------------------------------	-----

Life Cycle

Sales Start	11.05.2009
Predecessor	88027 / AJ65BT-64RD4

Additional Product Information

Binding Tariff Information	DEBTI-10685/21-1
BTI validity date	31.10.2024
Battery included	NO

Export Data

Legal Control (Dual Use List)	Not Listed
Country of Origin	Japan (JP)
Preference Status (Supplier Declaration)	Non EU

Environmental

REACH Limit Exceeded	YES
REACH Substance CAS Number	13560-89-9
REACH Substance CAS Number (2)	7439-92-1

REACH Substance CAS Number (3)	80-05-7
Dangerous Goods Class	NO
Dangerous Goods Identifier	NO
RoHS Compliance	COMPLIANT
WEEE	B2B

Conformity

CE	COMPLIANT
UL/cUL	COMPLIANT
EAC	COMPLIANT
UKCA	COMPLIANT

Documentation & Media Data

Manual URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=bltdae25c2bd5f2ff94&q=AJ65SBT2B-64RD3&doc-lang=en
Certificates URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt8050dd1408c11cc2&q=AJ65SBT2B-64RD3&doc-lang=en

Product Packaging

Cardboard (g)	80
Other paper (g)	1
Aluminum (g)	0
Steel (g)	0
Styrofoam (g)	0
Other plastic (g)	5
Wood (g)	0
Glass (g)	0
Others (g)	0