

MATERIAL FACT SHEET

279563 RD75P4

General Data

Product Hierarchy	IAD51401
	Modular PLC
	IQ-R Standard
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	B (Limited Availability from Stock)

e-shop: https://mitsubishi-electric-eshop.mee.com/mee/FA_IA/EUR/en/p/000000000000279563

FA-MOD PLC: Positioning Module

Series	MELSEC IQ-R SERIES
Type	TRANSISTOR OUTPUT
Number of Axes	4
Int. Current Consumption (A)	0,42

Product Dimensions & Weight

Width (mm)	27,8
Height (mm)	98 (106)
Depth (mm)	110
Weight (kg)	0,15

Logistic Dimensions & Gross Weight

Length (cm)	16,0
Width (cm)	15,0
Height (cm)	5,0
Gross Weight (kg)	0,228
Volume (cdm)	1,200

Stock Data

Planned Delivery Time (Days)	136
------------------------------	-----

Life Cycle

Sales Start	09.12.2014
Predecessor	No Predecessor

Additional Product Information

Binding Tariff Information	DEBTI-10930/21-1
BTI validity date	10.10.2024
Battery included	NO

Export Data

Legal Control (Dual Use List)	Not Listed
Country of Origin	Japan (JP)
Preference Status (Supplier Declaration)	Non EU

Environmental

REACH Limit Exceeded	YES
REACH Substance CAS Number	12060-00-3
REACH Substance CAS Number (2)	2451-62-9
REACH Substance CAS Number (3)	7439-92-1
Dangerous Goods Class	NO
Dangerous Goods Identifier	NO
RoHS Compliance	COMPLIANT
WEEE	B2B

Conformity

CE	COMPLIANT
UL/cUL	COMPLIANT
EAC	COMPLIANT
Shipping Approvals	ABS,BV,DNV,GL,LR,NK,RINA
UKCA	COMPLIANT

Documentation & Media Data

Manual URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=bltdae25c2bd5f2f94&q=RD75P4&doc-lang=en
Certificates URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt8050dd1408c11cc2&q=RD75P4&doc-lang=en
CAD URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt26ecc97a31a841c1&q=RD75P4&doc-lang=en

Product Packaging

Cardboard (g)	45
Other paper (g)	26
Aluminum (g)	0
Steel (g)	0
Styrofoam (g)	0
Other plastic (g)	5
Wood (g)	0
Glass (g)	0
Others (g)	0

Compatible products

Material	Description / Price List Text / Classification
134139	A6CON1 PLC Connection-plug for I/O-Modules Source-Input/Sink-Output, soldering Class 100100215: FA-MOD PLC: Other Option
134140	A6CON2 PLC Connection-plug for I/O-Modules Source-Input/Sink-Output, crimp Class 100100215: FA-MOD PLC: Other Option
140991	Q40CBL-3M PLC Connection cable 40-pin modules (A6CON-type), shielded, length 3 m, open end Class 100100214: FA-MOD PLC: Cable
140997	Q40CBL-5M PLC Connection cable 40-pin modules (A6CON-type), shielded, length 5 m open end Class 100100214: FA-MOD PLC: Cable
146923	A6CON4 PLC Connection-plug for I/O-Modules as A6CON-1 w/ 45 degree cable-outlet Class 100100215: FA-MOD PLC: Other Option
147699	FA-CBLQ75PM2J2 Readymade cable from QD75D1/D2/D4 and MR-C Servoamp Class 100100508: FA-Servo-Motion: Cable
158068	Q40CBL-10M PLC Connection cable 40-pin modules (A6CON-type), shielded, length 10 m open end Class 100100214: FA-MOD PLC: Cable
158069	Q40CBL-15M PLC Connection cable 40-pin modules (A6CON-type), shielded, length 15 m open end Class 100100214: FA-MOD PLC: Cable
275668	FA-CBLQ75PM2J3 System cable QD75P2/2N/4/4N,LD75P2/4 - MR-J3-A/MR-J4-A Class 100100508: FA-Servo-Motion: Cable
314841	Q40CBL-10M-S PLC Connection cable 40-pin modules(A6CON-type),10m,open,LiYY 40x0,14 mm²,flex Class 100100214: FA-MOD PLC: Cable
314842	Q40CBL-15M-S PLC Connection cable 40-pin modules(A6CON-type),15m open,LiYY 40x0,14 mm²,flex Class 100100214: FA-MOD PLC: Cable
594727	FA-CBL05Q7 PLC Connection cable; positioning modules to FA-LTBQ75M/FA-LTBQ75DP; 0,5m Class 100100214: FA-MOD PLC: Cable
594728	FA-CBL10Q7 PLC Connection cable; positioning modules to FA-LTBQ75M/FA-LTBQ75DP; 1m Class 100100214: FA-MOD PLC: Cable