



## MATERIAL FACT SHEET

### 221862 AJ65SBT2B-64RD3

#### General Data

|                     |                                        |
|---------------------|----------------------------------------|
| Product Hierarchy   | IAD50501                               |
|                     | Modular PLC                            |
|                     | A2C-PLC                                |
| Ext. Material Group | 10 STANDARD ITEM                       |
| ABC Indicator       | C (Non-Stock Material / Make-to-Order) |

e-shop: [https://mitsubishi-electric-eshop.mee.com/mee/FA\\_IA/EUR/en/p/000000000000221862](https://mitsubishi-electric-eshop.mee.com/mee/FA_IA/EUR/en/p/000000000000221862)

#### FA-MOD PLC: Temperature Module

|                              |                   |
|------------------------------|-------------------|
| Series                       | CC-LINK           |
| Type                         | TEMPERATURE INPUT |
| Power Supply (V)             | 24                |
| Current Type                 | DC                |
| Occupied Stations            | 1                 |
| Integrated Analogue Inputs   | 4                 |
| Input Type                   | RTD               |
| Applicable RTD Type          | JPT100            |
| Applicable RTD Type (2)      | NI100             |
| Applicable RTD Type (3)      | PT100             |
| Int. Current Consumption (A) | 0,14              |

#### Product Dimensions & Weight

|             |      |
|-------------|------|
| Width (mm)  | 122  |
| Height (mm) | 50   |
| Depth (mm)  | 54   |
| Weight (kg) | 0,25 |

#### Logistic Dimensions & Gross Weight

|                   |       |
|-------------------|-------|
| Length (cm)       | 13,5  |
| Width (cm)        | 8,5   |
| Height (cm)       | 10,0  |
| Gross Weight (kg) | 0,343 |
| Volume (cdm)      | 1,148 |

#### Stock Data

|                              |     |
|------------------------------|-----|
| Planned Delivery Time (Days) | 136 |
|------------------------------|-----|

#### Life Cycle

|             |                      |
|-------------|----------------------|
| Sales Start | 11.05.2009           |
| Predecessor | 88027 / AJ65BT-64RD4 |

#### Additional Product Information

|                            |                  |
|----------------------------|------------------|
| Binding Tariff Information | DEBTI-10685/21-1 |
| BTI validity date          | 31.10.2024       |
| Battery included           | NO               |

#### Export Data

|                                          |            |
|------------------------------------------|------------|
| Legal Control (Dual Use List)            | Not Listed |
| Country of Origin                        | Japan (JP) |
| Preference Status (Supplier Declaration) | Non EU     |

#### Environmental

|                                |                            |
|--------------------------------|----------------------------|
| REACH Limit Exceeded           | YES                        |
| REACH Substance CAS Number     | <a href="#">13560-89-9</a> |
| REACH Substance CAS Number (2) | <a href="#">7439-92-1</a>  |

|                                |           |
|--------------------------------|-----------|
| REACH Substance CAS Number (3) | 80-05-7   |
| Dangerous Goods Class          | NO        |
| Dangerous Goods Identifier     | NO        |
| RoHS Compliance                | COMPLIANT |
| WEEE                           | B2B       |

Conformity

|        |           |
|--------|-----------|
| CE     | COMPLIANT |
| UL/cUL | COMPLIANT |
| EAC    | COMPLIANT |
| UKCA   | COMPLIANT |

Documentation & Media Data

|                            |                                                                                                                                                                                                                                                                                                   |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Manual URL Indicator       | <a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=AJ65SBT2B-64RD3&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=AJ65SBT2B-64RD3&amp;doc-lang=en</a> |
| Certificates URL Indicator | <a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=AJ65SBT2B-64RD3&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=AJ65SBT2B-64RD3&amp;doc-lang=en</a> |

Product Packaging

|                   |    |
|-------------------|----|
| Cardboard (g)     | 80 |
| Other paper (g)   | 1  |
| Aluminum (g)      | 0  |
| Steel (g)         | 0  |
| Styrofoam (g)     | 0  |
| Other plastic (g) | 5  |
| Wood (g)          | 0  |
| Glass (g)         | 0  |
| Others (g)        | 0  |