



MATERIAL FACT SHEET

227966 LM-U2PBF-22M-1SS0

General Data

Product Hierarchy	IAK30214
	SERVO and Motion
	LM
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	C (Non-Stock Material / Make-to-Order)

e-shop: https://mitsubishi-electric-eshop.mee.com/mee/FA_1A/EUR/en/p/000000000000227966

FA-Servo-Motion: Linear Servo Motor

Series	MELSERVO-J4
Series (2)	MELSERVO-J5
Type	LM-U2
Rated Current (A)	4,6
Protection Class	IP00
Maximum Speed (m/s)	2
Side	PRIMARY
Power supply capacity (kVA)	1,3
Cooling method	NATURAL
Lenght (mm)	370
Rated thrust (N)	225
Maximum thrust (N)	675
Magnetic attraction force (N)	0
Maximum current (A)	13,7

Product Dimensions & Weight

Width (mm)	24,5
Height (mm)	86,5
Depth (mm)	370
Weight (kg)	1,1

Logistic Dimensions & Gross Weight

Length (cm)	0,0
Width (cm)	0,0
Height (cm)	0,0
Gross Weight (kg)	1,600
Volume (cdm)	0,000

Stock Data

Planned Delivery Time (Days)	100
------------------------------	-----

Life Cycle

Sales Start	22.09.2009
Predecessor	No Predecessor

Additional Product Information

Battery included	NO
------------------	----

Export Data

Commodity Code	85015220
Legal Control (Dual Use List)	Not Listed
Country of Origin	Japan (JP)
Preference Status (Supplier Declaration)	Non EU

Environmental

REACH Limit Exceeded	NO
----------------------	----

Dangerous Goods Class	NO
Dangerous Goods Identifier	NO
RoHS Compliance	COMPLIANT
WEEE	B2B

Conformity

CE	COMPLIANT
EAC	COMPLIANT
UKCA	COMPLIANT

Documentation & Media Data

Manual URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=bltdae25c2bd5f2ff94&q=LM-U2PBF-22M-1SS0&doc-lang=en
Certificates URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt8050dd1408c11cc2&q=L-M-U2PBF-22M-1SS0&doc-lang=en
CAD URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt26ecc97a31a841c1&q=LM-U2PBF-22M-1SS0&doc-lang=en

Product Packaging

Cardboard (g)	213
Other paper (g)	0
Aluminum (g)	0
Steel (g)	0
Styrofoam (g)	0
Other plastic (g)	40
Wood (g)	0
Glass (g)	0
Others (g)	0

Compatible products

Material	Description / Price List Text / Classification
161559	MR-EKCB20M-H Encoder cable; for HF-KE,-KN,-KP,-MP, HG-KR,-MR, high-flex 20m (motor shaft) Class 100100508: FA-Servo-Motion: Cable
161560	MR-EKCB30M-H Encoder cable; for HF-KE,-KN,-KP,-MP, HG-KR,-MR, high-flex 30m (motor shaft) Class 100100508: FA-Servo-Motion: Cable
161572	MR-ECNM Encoder-connector-set for HF-KE,-KN,-KP,-MP, HG-KN,-KR,-MR motor types Class 100100509: FA-Servo-Motion: Connector
192174	MR-J3CN2 Encoder-connector-set (for CN2L) Class 100100509: FA-Servo-Motion: Connector
227110	MR-J3THMCN2 Connector set for thermistor and linear encoder Class 100100509: FA-Servo-Motion: Connector
227970	LM-U2SB0-240-1SS0 Secondary Linear Servo Motor, 75/150/225N thrust,Length 240mm Class 100100512: FA-Servo-Motion: Linear Servo Motor
227971	LM-U2SB0-300-1SS0 Secondary Linear Servo Motor, 75/150/225N thrust,Length 300mm Class 100100512: FA-Servo-Motion: Linear Servo Motor
227972	LM-U2SB0-420-1SS0 Secondary Linear Servo Motor, 75/150/225N thrust,Length 420mm Class 100100512: FA-Servo-Motion: Linear Servo Motor
229788	MR-EKCB50M-H Encoder cable; for HF-KP(B)/HF-MP(B), high-flex 50m (lead out motor shaft), IP20 Class 100100508: FA-Servo-Motion: Cable
246915	MR-EKCB5M-H Encoder cable; high-flex, 5m, IP20 Class 100100508: FA-Servo-Motion: Cable
269075	MR-EKCB40M-H Class 100100508: FA-Servo-Motion: Cable
274005	MR-J4THCBL03M Junction Cable for MR-J4 with linear servo motor Class 100100508: FA-Servo-Motion: Cable
482030	MR-EKCB2M-H Encoder cable; Highflexible; 2 m; IP20; Class 100100508: FA-Servo-Motion: Cable