



MATERIAL FACT SHEET

283575 FFR-HEL-7.5K-E1

General Data

Product Hierarchy	IAK21201
	INVERTER
	NEW EXTERNAL OPTIONS
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	B (Limited Availability from Stock)

e-shop: https://mitsubishi-electric-eshop.mee.com/mee/FA_IA/EUR/en/p/000000000000283575

FA-Inverter: Choke

Type	DC LINK CHOKE
Applicable Inverter	FR-A741
Applicable Inverter (2)	FR-A800
Applicable Inverter (3)	FR-D700-SC
Applicable Inverter (4)	FR-E800
Applicable Inverter (5)	FR-F800
Rated Voltage (V)	200
Current Type	DC
Inductance (mH)	0,77
Rated Capacity (kW)	7,5
Rated Current (A)	34
Power Loss (W)	30,4
Protection Class	IP20

Product Dimensions & Weight

Width (mm)	133,2
Height (mm)	85
Depth (mm)	112
Weight (kg)	3,1

Logistic Dimensions & Gross Weight

Length (cm)	10,5
Width (cm)	12,5
Height (cm)	10,5
Gross Weight (kg)	3,410
Volume (cdm)	1,378

Stock Data

Planned Delivery Time (Days)	42
------------------------------	----

Life Cycle

Sales Start	30.01.2015
Predecessor	238363 / FFR-HEL-7.5K-E

Additional Product Information

Battery included	NO
------------------	----

Export Data

Commodity Code	85049090
Legal Control (Dual Use List)	Not Listed
Country of Origin	Slovenia (SI)
Preference Status (Supplier Declaration)	Non EU

Environmental

REACH Limit Exceeded	NO
Dangerous Goods Class	NO

Dangerous Goods Identifier	NO
RoHS Compliance	COMPLIANT
WEEE	B2B

Conformity

CE	COMPLIANT
----	-----------

Documentation & Media Data

Manual URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=bltdae25c2bd5f2ff94&q=FFR-HEL-7.5K-E1&doc-lang=en
Certificates URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt8050dd1408c11cc2&q=FFR-HEL-7.5K-E1&doc-lang=en