



## MATERIAL FACT SHEET

### 279243 S-T21 AC300V 2A2B

#### General Data

|                     |                                        |
|---------------------|----------------------------------------|
| Product Hierarchy   | IAN50201                               |
|                     | MC                                     |
|                     | S-T Body                               |
| Ext. Material Group | 10 STANDARD ITEM                       |
| ABC Indicator       | C (Non-Stock Material / Make-to-Order) |

e-shop: [https://mitsubishi-electric-eshop.mee.com/mee/FA\\_IJA/EUR/en/p/000000000000279243](https://mitsubishi-electric-eshop.mee.com/mee/FA_IJA/EUR/en/p/000000000000279243)

#### FA-MC: Magnetic Contactor

|                                |                                |
|--------------------------------|--------------------------------|
| Series                         | MS-T SERIES MAGNETIC CONTACTOR |
| Type                           | NON-REVERSING, AC OPERATED     |
| Frame Size                     | 21                             |
| Current Type                   | AC TYPE                        |
| Coil Voltage (V)               | 260-300                        |
| Rated Current (A)              | 3-PHASE AC690V: 9              |
| Rated Capacity (kW)            | 3-PHASE AC220-240V: 5.5        |
| Rated Capacity (kW) (2)        | 3-PHASE AC380-440V: 11         |
| Rated Capacity (kW) (3)        | 3-PHASE AC690V: 7.5            |
| Rated Voltage (V)              | 690                            |
| Number of Poles                | 3                              |
| No of Auxiliary Contacts NO    | 2                              |
| No of Auxiliary Contacts NC    | 2                              |
| Frequency Range (Hz)           | 50/60                          |
| Min. Ambient Temperature (°C)  | -10                            |
| Max. Ambient Temperature (°C)  | 40                             |
| Wiring                         | SCREW-CLAMP                    |
| Design / Styling               | STANDARD                       |
| Compliant with Standard(s)     | EN60947-4-1                    |
| Compliant with Standard(s) (2) | IEC60947-4-1                   |
| Compliant with Standard(s) (3) | JIS C8201-4-1                  |
| Electrical Durability (Load)   | -                              |
| Mech. Durability (at no Load)  | 10 000 000 OPERATIONS          |
| Protection Class               | IP20                           |

#### Product Dimensions & Weight

|             |      |
|-------------|------|
| Width (mm)  | 63   |
| Height (mm) | 81   |
| Depth (mm)  | 81   |
| Weight (kg) | 0,41 |

#### Logistic Dimensions & Gross Weight

|                   |       |
|-------------------|-------|
| Length (cm)       | 8,5   |
| Width (cm)        | 6,5   |
| Height (cm)       | 8,5   |
| Gross Weight (kg) | 0,423 |
| Volume (cdm)      | 0,470 |

#### Stock Data

|                              |     |
|------------------------------|-----|
| Planned Delivery Time (Days) | 280 |
|------------------------------|-----|

#### Life Cycle

|             |                |
|-------------|----------------|
| Sales Start | 28.11.2014     |
| Predecessor | No Predecessor |

#### Additional Product Information

|                  |    |
|------------------|----|
| Battery included | NO |
|------------------|----|

## Export Data

|                                          |            |
|------------------------------------------|------------|
| Legal Control (Dual Use List)            | Not Listed |
| Country of Origin                        | Japan (JP) |
| Preference Status (Supplier Declaration) | Non EU     |

## Environmental

|                            |           |
|----------------------------|-----------|
| REACH Limit Exceeded       | NO        |
| Dangerous Goods Class      | NO        |
| Dangerous Goods Identifier | NO        |
| RoHS Compliance            | COMPLIANT |
| WEEE                       | B2B       |

## Conformity

|        |           |
|--------|-----------|
| CE     | COMPLIANT |
| UL/cUL | COMPLIANT |
| EAC    | COMPLIANT |
| UKCA   | COMPLIANT |

## Documentation & Media Data

|                            |                                                                                                                                                                                                                                                                                                             |
|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Manual URL Indicator       | <a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=S-T21%20AC300V%20A2B&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=S-T21%20AC300V%20A2B&amp;doc-lang=en</a> |
| Certificates URL Indicator | <a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=S-T21%20AC300V%20A2B&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=S-T21%20AC300V%20A2B&amp;doc-lang=en</a> |
| CAD URL Indicator          | <a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt26ecc97a31a841c1&amp;q=S-T21%20AC300V%20A2B&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt26ecc97a31a841c1&amp;q=S-T21%20AC300V%20A2B&amp;doc-lang=en</a> |

## Product Packaging

|                   |     |
|-------------------|-----|
| Cardboard (g)     | 300 |
| Other paper (g)   | 0   |
| Aluminum (g)      | 0   |
| Steel (g)         | 0   |
| Styrofoam (g)     | 0   |
| Other plastic (g) | 1   |
| Wood (g)          | 0   |
| Glass (g)         | 0   |
| Others (g)        | 0   |

## Compatible products

| Material               | Description / Price List Text / Classification                                                                                                     |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| <a href="#">52634</a>  | UN-ML21<br>Mechanical interlock. For S(D)-N18 up to 65<br>Class 100101002: FA-MC: Mechanical Option                                                |
| 249115                 | UN-SY11<br>DC interface unit for operating coils<br>Class 100101003: FA-MC: Electrical Option                                                      |
| 249116                 | UN-SY12<br>DC interface unit for operating coils; for S-T10-T100/SR-T5,T9/S-N125-N400<br>Class 100101003: FA-MC: Electrical Option                 |
| <a href="#">279298</a> | TH-T25KP 0.24A<br>Overload Relay. Ith = 0,2 ~ 0,32A; for S(D)-T21, 25 (without Mountingset)<br>Class 100101005: FA-MC: Overload Protection Relays  |
| <a href="#">279299</a> | TH-T25KP 0.35A<br>Overload Relay. Ith = 0,28 ~ 0,42A; for S(D)-T21, 25 (without Mountingset)<br>Class 100101005: FA-MC: Overload Protection Relays |
| <a href="#">279300</a> | TH-T25KP 0.5A<br>Overload Relay. Ith = 0,4 ~ 0,6A; for S(D)-T21, 25 (without Mountingset)<br>Class 100101005: FA-MC: Overload Protection Relays    |
| <a href="#">279301</a> | TH-T25KP 0.7A<br>Overload Relay. Ith = 0,55 ~ 0,85A; for S(D)-T21, 25 (without Mountingset)<br>Class 100101005: FA-MC: Overload Protection Relays  |
| <a href="#">279302</a> | TH-T25KP 0.9A<br>Overload Relay. Ith = 0,7 ~ 1,1A; for S(D)-T21, 25 (without Mountingset)<br>Class 100101005: FA-MC: Overload Protection Relays    |
| <a href="#">279303</a> | TH-T25KP 1.3A<br>Overload Relay. Ith = 1,0 ~ 1,6A; for S(D)-T21, 25 (without Mountingset)<br>Class 100101005: FA-MC: Overload Protection Relays    |
| <a href="#">279304</a> | TH-T25KP 1.7A<br>Overload Relay. Ith = 1,4 ~ 2,0A; for S(D)-T21, 25 (without Mountingset)<br>Class 100101005: FA-MC: Overload Protection Relays    |

| Material               | Description / Price List Text / Classification                                                                                                   |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| <a href="#">279305</a> | TH-T25KP 2.1A<br>Overload Relay. Ith = 1,7 ~ 2,5A; for S(D)-T21, 25 (without Mountingset)<br>Class 100101005: FA-MC: Overload Protection Relays  |
| <a href="#">279306</a> | TH-T25KP 2.5A<br>Overload Relay. Ith = 2,0 ~ 3,0A; for S(D)-T21, 25 (without Mountingset)<br>Class 100101005: FA-MC: Overload Protection Relays  |
| <a href="#">279307</a> | TH-T25KP 3.6A<br>Overload Relay. Ith = 2,8 ~ 4,4A; for S(D)-T21, 25 (without Mountingset)<br>Class 100101005: FA-MC: Overload Protection Relays  |
| <a href="#">279308</a> | TH-T25KP 5A<br>Overload Relay. Ith = 4,0 ~ 6,0A; for S(D)-T21, 25 (without Mountingset)<br>Class 100101005: FA-MC: Overload Protection Relays    |
| <a href="#">279309</a> | TH-T25KP 6.6A<br>Overload Relay. Ith = 5,2 ~ 8,0A; for S(D)-T21, 25 (without Mountingset)<br>Class 100101005: FA-MC: Overload Protection Relays  |
| <a href="#">279310</a> | TH-T25KP 9A<br>Overload Relay. Ith = 7,0 ~ 11,0A; for S(D)-T21, 25 (without Mountingset)<br>Class 100101005: FA-MC: Overload Protection Relays   |
| <a href="#">279311</a> | TH-T25KP 11A<br>Overload Relay. Ith = 9,0 ~ 13,0A; for S(D)-T21, 25 (without Mountingset)<br>Class 100101005: FA-MC: Overload Protection Relays  |
| <a href="#">279312</a> | TH-T25KP 15A<br>Overload Relay. Ith = 12,0 ~ 18,0A; for S(D)-T21, 25 (without Mountingset)<br>Class 100101005: FA-MC: Overload Protection Relays |
| <a href="#">279313</a> | TH-T25KP 22A<br>Overload Relay. Ith = 18,0 ~ 26,0A; for S(D)-T21, 25 (without Mountingset)<br>Class 100101005: FA-MC: Overload Protection Relays |
| <a href="#">279314</a> | UT-AX11 1A1B<br>Auxiliary contact. 1NO + 1NC; side clip-on; for S-T, SR-T<br>Class 100101003: FA-MC: Electrical Option                           |
| <a href="#">279315</a> | UT-AX2 1A1B<br>Auxiliary contact. 1NO + 1NC; front clip-on; for S-T, SR-T<br>Class 100101003: FA-MC: Electrical Option                           |
| <a href="#">279316</a> | UT-AX2 2A<br>Auxiliary contact. 2NO; front clip-on; for S-T, SR-T<br>Class 100101003: FA-MC: Electrical Option                                   |
| <a href="#">279317</a> | UT-AX2 2B<br>Auxiliary contact. 2NC; front clip-on; for S-T, SR-T<br>Class 100101003: FA-MC: Electrical Option                                   |
| <a href="#">279318</a> | UT-AX4 2A2B<br>Auxiliary contact. 2NO + 2NC; front clip-on; for S-T, SR-T<br>Class 100101003: FA-MC: Electrical Option                           |
| <a href="#">279319</a> | UT-AX4 3A1B<br>Auxiliary contact. 3NO + 1NC; front clip-on; for S-T, SR-T<br>Class 100101003: FA-MC: Electrical Option                           |
| <a href="#">279320</a> | UT-AX4 4A<br>Auxiliary contact. 4NO; front clip-on; for S-T, SR-T<br>Class 100101003: FA-MC: Electrical Option                                   |
| <a href="#">279322</a> | UT-SA21 AC48V<br>Surge abs. Varistor; AC 24~50V, DC 24~220V; f. S-T, SR-T<br>Class 100101003: FA-MC: Electrical Option                           |
| <a href="#">279323</a> | UT-SA21 AC200V<br>Surge abs. Varistor; AC 100~240V, DC 24~220V; f. S-T, SR-T<br>Class 100101003: FA-MC: Electrical Option                        |
| <a href="#">279324</a> | UT-SA21 AC400V<br>Surge abs. Varistor; AC 346~480V; f. S-T, SR-T<br>Class 100101003: FA-MC: Electrical Option                                    |
| <a href="#">279325</a> | UT-SA22 AC200V<br>Surge abs. Varistor + LED; AC 100~240V, DC 24~220V; f. SS-T, SR-T<br>Class 100101003: FA-MC: Electrical Option                 |
| <a href="#">279326</a> | UT-SA23 AC200V<br>Surge abs. CR; AC 100~240V, DC 24~60V; f. S-T, SR-T<br>Class 100101003: FA-MC: Electrical Option                               |
| <a href="#">279327</a> | UT-SA25 AC48V<br>Surge abs. Varistor + CR; AC 24~50V, DC 100~250V; f. S-T, SR-T<br>Class 100101003: FA-MC: Electrical Option                     |
| <a href="#">279328</a> | UT-SA25 AC200V<br>Surge abs. Varistor + CR; AC 100~240V; f. S-T, SR-T<br>Class 100101003: FA-MC: Electrical Option                               |

| Material               | Description / Price List Text / Classification                                                                                               |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| <a href="#">293229</a> | UT-HZ18<br>Separate mounting adaptor for Thermal Overload Relays TN-T18<br>Class 100101003: FA-MC: Electrical Option                         |
| 316474                 | UN-FD4 DC24V 1A<br>UN-FD4 DC24V 1A<br>Class 100101003: FA-MC: Electrical Option                                                              |
| <a href="#">497349</a> | UT-SY21<br>DC interface module for S-T contactor; solid state output; direct mounting<br>Class 100101003: FA-MC: Electrical Option           |
| <a href="#">594864</a> | UN-TH21<br>Connecting bar kit S(D)-N20-21 with TH-N20KP/T25KP<br>Class 100101003: FA-MC: Electrical Option                                   |
| 599402                 | UT-AX2 1A1B<br>Auxiliary contact.1NO+1NC; front clip-on; for S-T,SR-T; without UL certification<br>Class 100101003: FA-MC: Electrical Option |
| 599403                 | UT-AX2 2A<br>Auxiliary contact. 2NO; front clip-on; for S-T, SR-T; without UL certification<br>Class 100101003: FA-MC: Electrical Option     |
| <a href="#">599404</a> | UT-AX2 2B<br>Auxiliary contact. 2NC; front clip-on; for S-T, SR-T; without UL certification<br>Class 100101003: FA-MC: Electrical Option     |
| 599405                 | UT-AX4 2A2B<br>Auxiliary contact.2NO+2NC; front clip-on; for S-T,SR-T; without UL certification<br>Class 100101003: FA-MC: Electrical Option |
| <a href="#">599406</a> | UT-AX4 3A1B<br>Auxiliary contact.3NO+1NC; front clip-on; for S-T,SR-T; without UL certification<br>Class 100101003: FA-MC: Electrical Option |
| <a href="#">599407</a> | UT-AX4 4A<br>Auxiliary contact. 4NO; front clip-on; for S-T, SR-T; without UL certification<br>Class 100101003: FA-MC: Electrical Option     |
| <a href="#">624863</a> | UN-SA33<br>Main Circuit Surge Absorber Unit; AC240; 50/60Hz; for Magnetic Contactors<br>Class 100101003: FA-MC: Electrical Option            |