



MATERIAL FACT SHEET

285503 R60DA16-G

General Data

Product Hierarchy	IAD51401
	Modular PLC
	IQ-R Standard
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	B (Limited Availability from Stock)

e-shop: https://mitsubishi-electric-eshop.mee.com/mee/FA_IA/EUR/en/p/000000000000285503

FA-MOD PLC: Analogue I/O Module

Series	MELSEC IQ-R SERIES
Type	CHANNEL ISOLATED ANALOG OUTPUT
Power Supply (V)	24
Current Type	DC
Occupied I/O Points on PLC	48
Integrated Analogue Outputs	16
Output Voltage Range (V)	-12-12; -10-10; 0-5; 1-5
Output Current Range (mA)	0-20; 4-20
Wiring	SCREW
Int. Current Consumption (A)	0,25

Product Dimensions & Weight

Width (mm)	56
Height (mm)	98 (106)
Depth (mm)	110
Weight (kg)	0,32

Logistic Dimensions & Gross Weight

Length (cm)	16,0
Width (cm)	15,0
Height (cm)	8,0
Gross Weight (kg)	0,449
Volume (cdm)	1,920

Stock Data

Planned Delivery Time (Days)	75
------------------------------	----

Life Cycle

Sales Start	27.03.2015
Predecessor	No Predecessor

Additional Product Information

Binding Tariff Information	DEBTI-10685/21-1
BTI validity date	31.10.2024
Battery included	NO

Export Data

Commodity Code	85389099
Legal Control (Dual Use Listed)	Not Listed
Country of Origin	Japan (JP)
Preference Status (Supplier Declaration)	Non EU

Environmental

REACH Limit Exceeded	YES
REACH Substance CAS Number	2451-62-9
REACH Substance CAS Number (2)	7439-92-1

Dangerous Goods Class	NO
Dangerous Goods Identifier	NO
RoHS Compliance	COMPLIANT
WEEE	B2B

Conformity

CE	COMPLIANT
UL/cUL	COMPLIANT
EAC	COMPLIANT
Shipping Approvals	ABS,BV,DNV GL,LR,NK,RINA
UKCA	COMPLIANT

Documentation & Media Data

Manual URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=bltdae25c2bd5f2ff94&q=R60DA16-G&doc-lang=en
Certificates URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt8050dd1408c11cc2&q=R60DA16-G&doc-lang=en
CAD URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt26ecc97a31a841c1&q=R60DA16-G&doc-lang=en

Product Packaging

Cardboard (g)	45
Other paper (g)	25
Aluminum (g)	0
Steel (g)	0
Styrofoam (g)	0
Other plastic (g)	3
Wood (g)	0
Glass (g)	0
Others (g)	0

Compatible products

Material	Description / Price List Text / Classification
134139	A6CON1 PLC Connection-plug for I/O-Modules Source-Input/Sink-Output, soldering Class 100100215: FA-MOD PLC: Other Option
134140	A6CON2 PLC Connection-plug for I/O-Modules Source-Input/Sink-Output, crimp Class 100100215: FA-MOD PLC: Other Option
140991	Q40CBL-3M PLC Connection cable 40-pin modules (A6CON-type), shielded, length 3 m, open end Class 100100214: FA-MOD PLC: Cable
140997	Q40CBL-5M PLC Connection cable 40-pin modules (A6CON-type), shielded, length 5 m open end Class 100100214: FA-MOD PLC: Cable
146923	A6CON4 PLC Connection-plug for I/O-Modules as A6CON-1 w/ 45 degree cable-outlet Class 100100215: FA-MOD PLC: Other Option
158068	Q40CBL-10M PLC Connection cable 40-pin modules (A6CON-type), shielded, length 10 m open end Class 100100214: FA-MOD PLC: Cable
158069	Q40CBL-15M PLC Connection cable 40-pin modules (A6CON-type), shielded, length 15 m open end Class 100100214: FA-MOD PLC: Cable
286266	FA-LTB40DAG PLC System-terminal; connector-terminal conversion unit (screw type) Class 100100299: FA-MOD PLC: Sets
314841	Q40CBL-10M-S PLC Connection cable 40-pin modules(A6CON-type),10m,open,LiYY 40x0,14 mm²,flex Class 100100214: FA-MOD PLC: Cable
314842	Q40CBL-15M-S PLC Connection cable 40-pin modules(A6CON-type),15m open,LiYY 40x0,14 mm²,flex Class 100100214: FA-MOD PLC: Cable
502506	FA1-CBL05R60DA8G PLC Connection cable; R60DA8-G/R60DA16-G to FA1-TBS40DAG/FA-LTB40DAG; 0,5m Class 100100214: FA-MOD PLC: Cable
502507	FA1-CBL10R60DA8G PLC Connection cable; R60DA8-G/R60DA16-G to FA1-TBS40DAG/FA-LTB40DAG; 1m Class 100100214: FA-MOD PLC: Cable

Material	Description / Price List Text / Classification
502508	FA1-CBL20R60DA8G PLC Connection cable; R60DA8-G/R60DA16-G to FA1-TBS40DAG/FA-LTB40DAG; 2m Class 100100214: FA-MOD PLC: Cable
502509	FA1-CBL30R60DA8G PLC Connection cable; R60DA8-G/R60DA16-G to FA1-TBS40DAG/FA-LTB40DAG; 3m Class 100100214: FA-MOD PLC: Cable
502510	FA1-TBS40DAG Terminal block conversion unit for Q66DA-G, R60DA8-G, R60DA16-G; screw type Class 100100215: FA-MOD PLC: Other Option