



## MATERIAL FACT SHEET

### 412465 FR-A842-07700-E2-60R2R

#### General Data

|                     |                                        |
|---------------------|----------------------------------------|
| Product Hierarchy   | IAK24103                               |
|                     | INVERTER                               |
|                     | FR-A840 from 2160                      |
| Ext. Material Group | 10 STANDARD ITEM                       |
| ABC Indicator       | C (Non-Stock Material / Make-to-Order) |

e-shop: [https://mitsubishi-electric-eshop.mee.com/mee/FA\\_IA/EUR/en/p/000000000000412465](https://mitsubishi-electric-eshop.mee.com/mee/FA_IA/EUR/en/p/000000000000412465)

#### FA-Inverter: Inverter

|                               |                                |
|-------------------------------|--------------------------------|
| Series                        | FR-A800 PLUS SERIES            |
| Type                          | FR-A800-R2R (FOR ROLL TO ROLL) |
| Minimum Rated Voltage (V)     | 430                            |
| Min. Permissible Voltage (V)  | 430                            |
| Maximum Rated Voltage (V)     | 780                            |
| Max. Permissible Voltage (V)  | 780                            |
| Current Type                  | DC                             |
| Phases                        | 3                              |
| Rated Output Current ND (A)   | 610                            |
| Rated Motor Capacity ND (kW)  | 315                            |
| Rated Motor Capacity HD (kW)  | 280                            |
| Frequency Range (Hz)          | 0,2-590                        |
| Control Method                | SOFT-PWM/HIGH FRQ PWM/VECTOR   |
| Motor Type                    | INDUCTION MOTOR                |
| Integrated EMC Filter         | YES                            |
| Safe Torque Off (STO)         | YES                            |
| Regenerative (4Q)             | NO                             |
| Integrated DC Choke           | NO                             |
| Display                       | FR-DU08                        |
| Display Type                  | 5 DIGITS LED                   |
| PLC Function                  | YES                            |
| Program Memory                | 6K                             |
| Program Memory Unit           | STEPS                          |
| Integrated Digital Inputs     | 12                             |
| Digital Outputs (Transistor)  | 5                              |
| Digital Outputs (Relay)       | 2                              |
| Integrated Analogue Inputs    | 3                              |
| Integrated Analogue Outputs   | 2                              |
| IO Type of Terminal Block     | SPRING CLAMP                   |
| Expandable                    | YES                            |
| USB                           | 2                              |
| Ethernet Port                 | 1                              |
| Built-In Network              | MODBUS-RTU                     |
| Leakage Current (mA)          | 35(DELTA) / 2(STAR)            |
| Power Loss SLD (W)            | 5800                           |
| Power Loss LD (W)             | 5050                           |
| Power Loss ND (W)             | 4450                           |
| Power Loss HD (W)             | 3900                           |
| Standby Power Consumption (W) | 80                             |
| Protection Class              | IP00                           |

#### Product Dimensions & Weight

|             |      |
|-------------|------|
| Width (mm)  | 540  |
| Height (mm) | 1330 |
| Depth (mm)  | 440  |
| Weight (kg) | 163  |

**Logistic Dimensions & Gross Weight**

|                   |         |
|-------------------|---------|
| Length (cm)       | 0,0     |
| Width (cm)        | 0,0     |
| Height (cm)       | 0,0     |
| Gross Weight (kg) | 192,060 |
| Volume (cdm)      | 0,000   |

**Stock Data**

|                              |     |
|------------------------------|-----|
| Planned Delivery Time (Days) | 156 |
|------------------------------|-----|

**Life Cycle**

|             |                                |
|-------------|--------------------------------|
| Sales Start | 07.01.2019                     |
| Predecessor | 296486 / FR-A842-07700-2-60R2R |

**Additional Product Information**

|                            |                      |
|----------------------------|----------------------|
| Difference to Standard 1   | ROLL TO ROLL CONTROL |
| Binding Tariff Information | DEBTI-19524/22-1     |
| BTI validity date          | 14.05.2026           |
| Battery included           | NO                   |
| Forecast Breakdown         | FR-A840 FROM 2160    |

**Export Data**

|                                          |            |
|------------------------------------------|------------|
| Commodity Code                           | 85371091   |
| Legal Control (Dual Use List)            | Not Listed |
| Country of Origin                        | Japan (JP) |
| Preference Status (Supplier Declaration) | Non EU     |

**Environmental**

|                            |           |
|----------------------------|-----------|
| Dangerous Goods Class      | NO        |
| Dangerous Goods Identifier | NO        |
| RoHS Compliance            | COMPLIANT |
| WEEE                       | B2B       |

**Conformity**

|        |           |
|--------|-----------|
| CE     | COMPLIANT |
| UL/cUL | COMPLIANT |
| EAC    | COMPLIANT |
| UKCA   | COMPLIANT |

**Documentation & Media Data**

|                                |                                                                                                                                                                                                                                                                                                                 |
|--------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Manual URL Indicator           | <a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=FR-A842-07700-E2-60R2R&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=FR-A842-07700-E2-60R2R&amp;doc-lang=en</a> |
| Certificates URL Indicator     | <a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=FR-A842-07700-E2-60R2R&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=FR-A842-07700-E2-60R2R&amp;doc-lang=en</a> |
| CAD URL Indicator              | <a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt26ecc97a31a841c1&amp;q=FR-A842-07700-E2-60R2R&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt26ecc97a31a841c1&amp;q=FR-A842-07700-E2-60R2R&amp;doc-lang=en</a> |
| Network configuration file URL | <a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blte8cf990c7c524b4e&amp;q=FR-A842-07700-E2-60R2R&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blte8cf990c7c524b4e&amp;q=FR-A842-07700-E2-60R2R&amp;doc-lang=en</a> |

**Product Packaging**

|                   |       |
|-------------------|-------|
| Cardboard (g)     | 21000 |
| Other paper (g)   | 0     |
| Aluminum (g)      | 0     |
| Steel (g)         | 50    |
| Styrofoam (g)     | 0     |
| Other plastic (g) | 395   |
| Wood (g)          | 0     |
| Glass (g)         | 0     |
| Others (g)        | 800   |

**Spare parts**

| Material               | Description                              | Quantity | Unit |
|------------------------|------------------------------------------|----------|------|
| <a href="#">282925</a> | FR-A840-04320-2-60 PCB POWER             | 1        | PC   |
| 282929                 | FR-A840-04320-12120/CC2 FUSE HOLDER      | 4        | PC   |
| <a href="#">282930</a> | FR-A840-04320-12120/CC2 FUSE             | 4        | PC   |
| <a href="#">282932</a> | FR-A840/842/846-ALL TERMINAL BLOCK A80TA | 1        | PC   |
| <a href="#">282935</a> | FR-A842-07700-2-60 / CC2-315K DCCT       | 3        | PC   |
| <a href="#">282940</a> | FR-A840/842/CC2-ALL CASE CPU             | 1        | PC   |
| <a href="#">282942</a> | FR-A840-03250-12120 BALANCE RESISTOR     | 16       | PC   |
| 282943                 | FR-A842-07700-08660 / CC2 ALL THERMISTOR | 1        | PC   |

| Material               | Description                              | Quantity | Unit |
|------------------------|------------------------------------------|----------|------|
| <a href="#">283444</a> | FR-A840-03250-12120-2-60 IGBT CM450DY207 | 15       | PC   |
| <a href="#">283484</a> | FR-A840-00770-2-60 OR BIGGER CBL MA-CPU  | 1        | PC   |
| <a href="#">283680</a> | FR-A842-ALL FUSE 6.9URD32TTF0900         | 4        | PC   |

### Compatible products

| Material               | Description / Price List Text / Classification                                                                                              |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| <a href="#">70727</a>  | FR-A5 CBL 1<br>Cable for connecting Inverter and Programming panel; 1m<br>Class 100100405: FA-Inverter: Cable                               |
| <a href="#">70728</a>  | FR-A5 CBL 2,5<br>Cable for connecting Inverter and Programming panel; 2,5m<br>Class 100100405: FA-Inverter: Cable                           |
| <a href="#">70729</a>  | FR-A5 CBL 5<br>Cable for connecting Inverter and Programming panel; 5m<br>Class 100100405: FA-Inverter: Cable                               |
| <a href="#">88426</a>  | SC-FR-PC CONNECTION CABLE PC>INVERTER<br>Programming Cable RS 232>RS485/422; 5m<br>Class 100100405: FA-Inverter: Cable                      |
| <a href="#">104666</a> | FN 3359-1000-99 f.A-280-375K/F-375K<br>Radio Noise Filter for FR-A&F-06830-09620; C2 100m; C4 100m<br>Class 100100404: FA-Inverter: Filter  |
| <a href="#">157515</a> | FR-ADP<br>Adaptor Module for Operator Panel FR-DU07<br>Class 100100403: FA-Inverter: External Option                                        |
| <a href="#">167612</a> | FR-RJ45-HUB10<br>Distribution Module for RJ45; 10 way<br>Class 100100403: FA-Inverter: External Option                                      |
| <a href="#">167613</a> | FR-RJ45-HUB4<br>Distribution Module for RJ45; 4 way<br>Class 100100403: FA-Inverter: External Option                                        |
| <a href="#">167614</a> | FR-RJ45-TR<br>Terminal Resistor Plug RJ45<br>Class 100100403: FA-Inverter: External Option                                                  |
| <a href="#">209749</a> | FFR-SI-683A-SS1<br>Sinusfilter for 400V Inverters; max. 683A; FT=2-16kHz; (W*H*D) 620*745*max.550mm<br>Class 100100404: FA-Inverter: Filter |
| <a href="#">209764</a> | FFR-DT-683A-SS1<br>du/dt Filter for 400V Inverters; max. 683A; FT=2-16kHz; (W*H*D) 240*325*230mm<br>Class 100100404: FA-Inverter: Filter    |
| <a href="#">221540</a> | USB-CAB-5M<br>USB 2.0 connection cabel, plug USB A to plug USB B (mini), 5m<br>Class 100100303: FA-HMI: Cable                               |
| <a href="#">262948</a> | A8NDPV1<br>Profibus DPV1 with Dsub Interface for FR-A/F800<br>Class 100100402: FA-Inverter: Internal Option                                 |
| <a href="#">262949</a> | A8NPRT_2P<br>Profinet 2port Interface for FR-A/F800 with Drive Profile<br>Class 100100402: FA-Inverter: Internal Option                     |
| <a href="#">262950</a> | A8NEIP_2P<br>EtherNet/IP 2port Interface for FR-A/F800<br>Class 100100402: FA-Inverter: Internal Option                                     |
| <a href="#">269426</a> | FR-A8AX<br>16-Bit-Digital-Input; BCD/Binary-Code; 24V DC; 5mA for FR-F/A800<br>Class 100100402: FA-Inverter: Internal Option                |
| <a href="#">269427</a> | FR-A8AY<br>Digital-/Analog Output; Output load: 24V DC; 0,1A for FR-F/A800<br>Class 100100402: FA-Inverter: Internal Option                 |
| <a href="#">269428</a> | FR-A8AR<br>Relay output; 3 additional output relays for FR-A/F800<br>Class 100100402: FA-Inverter: Internal Option                          |
| <a href="#">269431</a> | FR-A8NC<br>CC-Link Interface for FR-A/F800<br>Class 100100402: FA-Inverter: Internal Option                                                 |
| <a href="#">269432</a> | FR-A8ND<br>DeviceNet Interface for FR-A/F800<br>Class 100100402: FA-Inverter: Internal Option                                               |
| <a href="#">270295</a> | FR-HC2-H400K KIT<br>Harmonic Converter 400kW for Power Factor correction; 400V Class; KIT<br>Class 100100403: FA-Inverter: External Option  |

| Material               | Description / Price List Text / Classification                                                                                                                     |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <a href="#">273102</a> | FR-A8NCE<br>CC-Link IE Field Interface for FR-A/F800<br>Class 100100402: FA-Inverter: Internal Option                                                              |
| <a href="#">273314</a> | FR-HEL-H355K<br>DC Link choke for 400V Inverter with 355kW Motor<br>Class 100100406: FA-Inverter: Choke                                                            |
| <a href="#">274507</a> | FR-CC2-H315K-60<br>AC/DC Rectifier; Pn: 315kW; 3x380-500V; int. DC Choke; IP00; 200%60s/250%3s<br>Class 100100403: FA-Inverter: External Option                    |
| <a href="#">274514</a> | FR-A8NP<br>ProfibusDP Interface for FR-A/F800 with FR-A/F700 PPO types<br>Class 100100402: FA-Inverter: Internal Option                                            |
| <a href="#">274526</a> | FR-A8TAT<br>Adapter for control terminal of A/F700 to A/F800<br>Class 100100402: FA-Inverter: Internal Option                                                      |
| <a href="#">275503</a> | FR Configurator-M+FR-Configurator2<br>FR-Configurator for 700 series; multi I + FR-Configurator2 for 800 series<br>Class 100101203: FA-Software: Software Inverter |
| <a href="#">283940</a> | FR-A8AZ<br>Analog Input/ output, Thermistor interface<br>Class 100100402: FA-Inverter: Internal Option                                                             |
| <a href="#">284809</a> | A8NECT_2P<br>Ethercat 2port Interface for FR-A/F800<br>Class 100100402: FA-Inverter: Internal Option                                                               |
| <a href="#">290115</a> | FR-A8NCN<br>Control Net Interface for FR-A800 series<br>Class 100100402: FA-Inverter: Internal Option                                                              |
| <a href="#">290116</a> | FR-A8TR<br>Screw Terminal Block for FR-A/F800<br>Class 100100402: FA-Inverter: Internal Option                                                                     |
| <a href="#">294939</a> | FR-D-Sub9-A8NP-01<br>D-Sub9 Connection Adapter for FR-A8NP + Cover<br>Class 100100402: FA-Inverter: Internal Option                                                |
| <a href="#">296613</a> | FR-LU08-01<br>Clear text LCD Parameter unit for all units of 800 Series (IP55)<br>Class 100100403: FA-Inverter: External Option                                    |
| <a href="#">307170</a> | FR-A8ERS-60<br>Optioncard to change Ethernet board to serial communication<br>Class 100100402: FA-Inverter: Internal Option                                        |
| <a href="#">403133</a> | FR-A8AVP<br>Phase detection option board of FR-A/F800<br>Class 100100402: FA-Inverter: Internal Option                                                             |
| <a href="#">403134</a> | FR-A8VPB-H<br>Phase detection transformer box for FR-A8AVP<br>Class 100100403: FA-Inverter: External Option                                                        |
| <a href="#">487882</a> | FR-A8NCG<br>Plug-in Option for CC-Link IE TSN Communication Function<br>Class 100100402: FA-Inverter: Internal Option                                              |
| <a href="#">594984</a> | S-N600AB AC200V 2A2B<br>Magnetic contactor. 330kW; 2NO + 2NC; Us = AC 200V, 50Hz; Non-Reversing<br>Class 100101001: FA-MC: Magnetic Contactor                      |
| <a href="#">596902</a> | RHF-5P 355-400-50-00-S<br>High efficient double-stage passive harmonic filter for THDi <5%;400V;50Hz;355kW<br>Class 100100404: FA-Inverter: Filter                 |
| <a href="#">596909</a> | RHF-8P 355-400-50-00-S<br>High efficient double-stage passive harmonic filter for THDi <8%;400V;50Hz;355kW<br>Class 100100404: FA-Inverter: Filter                 |