



MATERIAL FACT SHEET

296225 FR-BAL-B3-55K

General Data

Product Hierarchy	IAK21201
	INVERTER
	NEW EXTERNAL OPTIONS
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	B (Limited Availability from Stock)

e-shop: https://mitsubishi-electric-eshop.mee.com/mee/FA_IA/EUR/en/p/000000000000296225

FA-Inverter: Choke

Type	AC MAIN SUPPLY CHOKE
Applicable Inverter	FR-A741
Applicable Inverter (2)	FR-A800
Applicable Inverter (3)	FR-D700-SC
Applicable Inverter (4)	FR-E800
Applicable Inverter (5)	FR-F800
Rated Voltage (V)	400
Current Type	AC
Phases	3
Inductance (mH)	0,221
Rated Capacity (kW)	55
Rated Current (A)	106
Power Loss (W)	APROX. 145
Protection Class	IP00

Product Dimensions & Weight

Width (mm)	210
Height (mm)	185
Depth (mm)	190
Weight (kg)	16

Logistic Dimensions & Gross Weight

Length (cm)	36,0
Width (cm)	30,0
Height (cm)	25,0
Gross Weight (kg)	16,500
Volume (cdm)	27,000

Stock Data

Planned Delivery Time (Days)	45
------------------------------	----

Life Cycle

Sales Start	04.04.2016
Predecessor	No Predecessor

Additional Product Information

Battery included	NO
------------------	----

Export Data

Commodity Code	85049090
Legal Control (Dual Use List)	Not Listed
Country of Origin	Germany (DE)
Preference Status (Supplier Declaration)	Non EU

Environmental

REACH Limit Exceeded	NO
----------------------	----

Dangerous Goods Class	NO
Dangerous Goods Identifier	NO
WEEE	B2B

Conformity

CE	COMPLIANT
UKCA	NON-COMPLIANT

Documentation & Media Data

Manual URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=bltdae25c2bd5f2ff94&q=FR-BAL-B3-55K&doc-lang=en
Certificates URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt8050dd1408c11cc2&q=FR-BAL-B3-55K&doc-lang=en
CAD URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt26ecc97a31a841c1&q=FR-BAL-B3-55K&doc-lang=en