



## MATERIAL FACT SHEET

265625 NV125-CV 3P 100A 2-440V 1.2.500MA JIEN C

### General Data

|                     |                                     |
|---------------------|-------------------------------------|
| Product Hierarchy   | IAN10203                            |
|                     | MCCB                                |
|                     | WS-V 1 - NV Body                    |
| Ext. Material Group | 10 STANDARD ITEM                    |
| ABC Indicator       | B (Limited Availability from Stock) |

e-shop: [https://mitsubishi-electric-eshop.mee.com/mee/FA\\_IJ/EUR/en/p/000000000000265625](https://mitsubishi-electric-eshop.mee.com/mee/FA_IJ/EUR/en/p/000000000000265625)

### FA-MCCB: Earth Leakage Circuit Breaker

|                                |                           |
|--------------------------------|---------------------------|
| Series                         | WS-V SERIES - ELCB        |
| Type                           | NV-C TYPE (ECONOMY CLASS) |
| Frame Size                     | 125                       |
| Rated Current (A)              | 100                       |
| Current Type                   | AC                        |
| Number of Poles                | 3                         |
| Rated Voltage (V)              | 2-440                     |
| Rated Current Sensibility (mA) | 100/200/500               |
| Max. Operating Time (s)        | 0,04                      |
| Pulsating Current Sensibility  | A (HARMONIC SURGE READY)  |
| Breaking Capacity at 400V (kA) | 10/5                      |
| Compliant with Standard(s)     | EN 60947-2                |
| Compliant with Standard(s) (2) | IEC 60947-2               |
| Cycles with Rated Current      | 6000                      |
| Cycles without Rated Current   | 10000                     |
| Automatic Tripping Device      | THERMAL-MAGNETIC          |

### Product Dimensions & Weight

|             |     |
|-------------|-----|
| Width (mm)  | 90  |
| Height (mm) | 130 |
| Depth (mm)  | 90  |
| Weight (kg) | 1   |

### Logistic Dimensions & Gross Weight

|                   |       |
|-------------------|-------|
| Length (cm)       | 13,0  |
| Width (cm)        | 10,0  |
| Height (cm)       | 9,5   |
| Gross Weight (kg) | 0,971 |
| Volume (cdm)      | 1,235 |

### Stock Data

|                              |     |
|------------------------------|-----|
| Planned Delivery Time (Days) | 104 |
|------------------------------|-----|

### Life Cycle

|             |                |
|-------------|----------------|
| Sales Start | 18.07.2013     |
| Predecessor | No Predecessor |

### Additional Product Information

|                  |    |
|------------------|----|
| Battery included | NO |
|------------------|----|

### Export Data

|                                          |            |
|------------------------------------------|------------|
| Commodity Code                           | 85362010   |
| Legal Control (Dual Use List)            | Not Listed |
| Country of Origin                        | Japan (JP) |
| Preference Status (Supplier Declaration) | Non EU     |

### Environmental

|                            |           |
|----------------------------|-----------|
| REACH Limit Exceeded       | NO        |
| Dangerous Goods Class      | NO        |
| Dangerous Goods Identifier | NO        |
| RoHS Compliance            | COMPLIANT |
| WEEE                       | B2C       |

### Conformity

|                    |               |
|--------------------|---------------|
| CE                 | COMPLIANT     |
| UL/cUL             | NON-COMPLIANT |
| Shipping Approvals | NON-COMPLIANT |
| UKCA               | COMPLIANT     |

### Documentation & Media Data

|                            |                                                                                                                                                                                                                                                                                                                                                                             |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Manual URL Indicator       | <a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=NV125-CV%203P%20100A%202-440V%201.2.500MA%20JIEN%20C&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=NV125-CV%203P%20100A%202-440V%201.2.500MA%20JIEN%20C&amp;doc-lang=en</a> |
| Certificates URL Indicator | <a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=NV125-CV%203P%20100A%202-440V%201.2.500MA%20JIEN%20C&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=NV125-CV%203P%20100A%202-440V%201.2.500MA%20JIEN%20C&amp;doc-lang=en</a> |
| CAD URL Indicator          | <a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt26ecc97a31a841c1&amp;q=NV125-CV%203P%20100A%202-440V%201.2.500MA%20JIEN%20C&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt26ecc97a31a841c1&amp;q=NV125-CV%203P%20100A%202-440V%201.2.500MA%20JIEN%20C&amp;doc-lang=en</a> |

### Product Packaging

|                   |    |
|-------------------|----|
| Cardboard (g)     | 69 |
| Other paper (g)   | 0  |
| Aluminum (g)      | 0  |
| Steel (g)         | 0  |
| Styrofoam (g)     | 0  |
| Other plastic (g) | 0  |
| Wood (g)          | 0  |
| Glass (g)         | 0  |
| Others (g)        | 0  |